

1 LOCATION OF WATER WELL:		Fraction County: GRAY	SW $\frac{1}{4}$	SE $\frac{1}{4}$	SW $\frac{1}{4}$	Section Number 11	Township Number T 26 S	Range Number R 28 <b>EW</b>
Distance and direction from nearest town or city street address of well if located within city? 1/2 South and 1/2 West of Cimarron, Kansas								
2 WATER WELL OWNER:		Mr. R. T. McElreath						
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources						
City, State, ZIP Code :		Cimarron, Kansas 67835 Application Number: ---						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL... 120 ft. ELEVATION: ... Slope.						
		Depth(s) Groundwater Encountered 1. Not available ft. 2. ft. 3. ft.						
		WELL'S STATIC WATER LEVEL ... 5 ft. below land surface measured on mo/day/yr April 27, 1987.						
		Pump test data: Well water was ft. after hours pumping gpm						
		Est. Yield 20. gpm: Well water was ft. after hours pumping gpm						
		Bore Hole Diameter 10 in. to 120 ft. and in. to ft.						
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
		XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well						
		Was a chemical/bacteriological sample submitted to Department? Yes No XX. If yes, mo/day/yr sample was submitted						
		Water Well Disinfected? Yes XX No						
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped				
1 Steel		3 RMP (SR)	6 Asbestos-Cement	Welded				
XX PVC		4 ABS	7 Fiberglass	Threaded				
Blank casing diameter 5 in. to 90 ft. Dia		in. to ft. Dia in. to ft.						
Casing height above land surface 25 in., weight 2.8 lbs./ft.		Wall thickness or gauge No. 265						
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC 10 Asbestos-cement						
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)			
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes				
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)				
SCREEN-PERFORATED INTERVALS:		From 90 ft. to 120 ft.	From	ft. to	ft. to	ft. to	ft. to	ft.
GRAVEL PACK INTERVALS:		From 50 ft. to 120 ft.	From	ft. to	ft. to	ft. to	ft. to	ft.
6 GROUT MATERIAL:		Neat cement	2 Cement grout	XX 3 Bentonite	4 Other			
Grout Intervals:		From 0 ft. to 50 ft.	From	ft. to	ft. to	ft. to	ft. to	ft.
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well						
XX Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well			
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)			
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage				
Direction from well?		How many feet? 150						
FROM	TO	LITHOLOGIC LOG			FROM	TO	LITHOLOGIC LOG	
0	2	Topsoil						
2	6	Fine Sand						
6	50	Lg. Sand & Gravel						
50	94	Sandy Clay						
94	119	Med. to Lar. Sand & Gravel						
119	120	Black Shale						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:		This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 27, 1987. and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252. This Water Well Record was completed on (mo/day/year) April 30, 1987. under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.								

12-8600000154