

CIM45

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: Gray NE 1/4 NE 1/4 NE 1/4	Section Number 12	Township Number T 26 S	Range Number R 28 NW
Distance and direction from nearest town or city street address of well if located within city? East Ave "A" - North Seventh - Blk 12 - Lot 16 - Reeve's Add't					
2 WATER WELL OWNER:		Willa Butcher			
RR#, St. Address, Box #:		Box 386			
City, State, ZIP Code:		Cimarron, KS 67835			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 58 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 37 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr 3-5-90 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 3 RMP (SR) 2 PVC 4 ABS	6 Concrete tile 6 Asbestos-Cement 7 Fiberglass	8 Other (specify below)	CASING JOINTS: Glued Clamped Welded Threaded
Blank casing diameter 10 in. to ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 30 ft. below in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel		5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.					
From ft. to ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.					
From ft. to ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.	2 Cement grout What is the nearest source of possible contamination:	3 Bentonite 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	4 Other 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) How many feet?
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit					
Direction from well?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
This well consisted of 30ft pit - 6'X6' - 28ft of casing - filled well casing with chlorinated sand 23ft to water level - Bentonite plug from 23ft to 28ft - top of casing and mushroomed Bentonite filled pit with 29ft of sand - 1ft of concrete over top of pit. Bentonite grout over bottom of pit 6'X6'X 1'					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-15-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 3-15-90 under the business name of <i>Dee's Well Service, Inc. Cimarron, KS.</i> by (signature) <i>Julie Creek</i>					