

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

Location.

1. Location of well:	County	Fraction	Section number	Township number	Range number
	Gray	SE 1/4 SW 1/4 SW 1/4	#13	T #26	S R # W
2. Distance and direction from nearest town or city:	1 1/2 south of Cimarron, Ks. on Highway 23		3. Owner of well:	Virgel Koehn	
Street address of well location if in city:			R.R. or street:		
4. Locate with "X" in section below:	Sketch map:		6. Bore hole dia. 8 in. Completion date 8-12-76 Well depth 210 ft.		
			7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
5. Type and color of material	From	To	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Top soil & fine sand	0	15	9. Casing: Material RMP Height: Above ground 2500 Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight lbs./ft. Dia. 5 in. to 210 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 250		
Coarse sand	15	30	10. Screen: Manufacturer's name Sunflower Type RMP Dia. 5" Slot <input type="checkbox"/> 1/8" Length 20 ft. Set between 215 ft. and 235 ft. ft. and ft. Gravel pack? yes Size range of material 1"		
Coarse sand	30	75	11. Static water level: mo./day/yr. 70 ft. below land surface Date 8-12-76		
Clay	75	120	12. Pumping level below land surfaces: 85 ft. after 1 hrs. pumping 100 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 150 g.p.m.		
Fine sand	120	150	13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No Date		
Clay	150	165	14. Well head completion: <input type="checkbox"/> Pitless adapter 21 Inches above grade		
Clay & coarse sand	165	225	15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 40 ft.		
Coarse sand, clay & blue shale	225	240	16. Nearest source of possible contamination: ft. 75 Direction South Type Sewer Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
(Use a second sheet if needed)			17. Pump: Manufacturer's name Flint & Walling Model number 15BK12 HP 15 Volts 230 Length of drop pipe 168 ft. capacity 19 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Joe's Well Service 179 Business name <input type="checkbox"/> License No. Address Box 174 Cimarron, Ks. Signed <input type="checkbox"/> Date 8-25-76 Authorized representative		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley					