


1 LOCATION OF WATER WELL: County: GRAY	Fraction SW 1/4 SW 1/4 SE 1/4	Section Number 14	Township Number T 26 S	Range Number R 28 EW
--	--------------------------------------	--------------------------	-------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?

3/4 m s. hwy 23 1/10 m. west 1 mile south OF CIMARRON

2 WATER WELL OWNER: GLORIA UNRUH RR#, St. Address, Box # : CIMARRON, KS. City, State, ZIP Code :	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;">N 1 Mile W E S</div> 	4 DEPTH OF COMPLETED WELL 200 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ... 47 ft. below land surface measured on mo/day/yr ... 9/24/87 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter ... 9 7/8 in. to ... 205 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No
---	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron <input checked="" type="checkbox"/> PVC 4 ABS 6 Asbestos-Cement Blank casing diameter 5 in. to 170 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 20 in., weight 200 lbs./ft. Wall thickness or gauge No.	7 Fiberglass TYPE OF SCREEN OR PERFORATION MATERIAL: <input checked="" type="checkbox"/> 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <input checked="" type="checkbox"/> Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded
SCREEN-PERFORATED INTERVALS: From 170 ft. to 200 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 50 ft. to 200 ft., From ft. to ft. From ft. to ft., From ft. to ft.		

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <input checked="" type="checkbox"/> Bentonite 4 Other Grout Intervals: From 4 ft. to 25 ft., From ft. to ft., From ft. to ft.	What is the nearest source of possible contamination: <input checked="" type="checkbox"/> Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage	Direction from well? east How many feet? 100
---	--	--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	COURSE GRABEL (LOOSE)			
20	28	FINE SAND AND GRAVEL (HARD STREAK ROCK)			
28	40	COURSE GRAVEL (LOOSE)			
40	88	BROWN SANDY CLAY (FEW HARD STREAKS)			
88	92	FINE TO MED SAND AND GRAVEL (LOOSE)			
92	102	BROWN SANDY CLAY			
102	118	FINE TO MED SAND AND GRAVEL (LOOSE)			
118	161	BROWN SANDY CLAY			
161	200	FINE TO MED SAND AND GRAVEL MIXED WITH BROWN AND WHITE ROCK			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... 10/10/87 ... and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 172 This Water Well Record was completed on (mo/day/yr) ... 6/88 ... under the business name of JONAGAN DRILLING CO. by (signature) <i>[Signature]</i>	
---	--