

1 LOCATION OF WATER WELL:	Fraction SW $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 16	Township Number T 26 S	Range Number R 28 E
---------------------------	--	----------------------	---------------------------	------------------------

County: Gray Distance and direction from nearest town or city street address of well if located within city?From Cimarron, South edge of Cimarron 1  $\frac{3}{4}$  miles west, and  $\frac{1}{4}$  mile south2 WATER WELL OWNER: Wiley McFarlandRR#, St. Address, Box #: Rt. 1City, State, ZIP Code: Cimarron, KS. 67835Board of Agriculture, Division of Water Resources  
Application Number:3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
4 DEPTH OF COMPLETED WELL: 75' ft. ELEVATION: .....

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 39' ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 7 1/2" in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes  No  If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes  No5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued  Clamped .....

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded .....

2 PVC 4 ABS 7 Fiberglass Threaded .....

Blank casing diameter: 5" in. to ft. Dia in. to ft. Dia in. to ft.Casing height above land surface: 2' in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .....

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) .....

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 13 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes .....

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .....

SCREEN-PERFORATED INTERVALS: From: 55' ft. to 75' ft. From: ft. to ft. From: ft. to ft.

From: ft. to ft. From: ft. to ft. From: ft. to ft.

GRAVEL PACK INTERVALS: From: 20' ft. to 75' ft. From: ft. to ft. From: ft. to ft.

From: ft. to ft. From: ft. to ft. From: ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .....

Grout Intervals: From: 0 ft. to 20 ft., From: ft. to ft., From: ft. to ft., From: ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage .....

Direction from well? west How many feet? 12'

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 Sandy Tepsil

2 27 Med. Sand

27 52 Med. Sand + Sandrock layers

52 72 Med. Course Sand

72 74 White Clay

74 80 Med. Sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-14-92 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 533 This Water Well Record was completed on (mo/day/yr) 11-24-92under the business name of Jardine Water Well Repair by (signature) [Signature]