


USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

T R EW sec 1/4 1/4 1/4 No.

Kansas State Dept. of Health  
(Water Well Contractors)  
Forbes-Bldg. 740  
Topeka, Kansas 66620

1 Location of well:	County Gray	Township name Cimarron	Fraction Pivot NE 1/4	Section number 20	Town number T 26 S	Range number R 28 W
Distance and direction from nearest town or city: Across river bridge at Cimarron, Ks., first road west to dead end, 1 1/4 south, 1/4 west				3 Owner of well: Louie Beery Address: Cimarron, Ks. 67835		
Locate with "X" in section below: 				Sketch map:		
4 Well depth: 246 ft. Date of completion 5-1-75 Well diameter 26 in.						
5 <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary						
6 Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Commercial <input type="checkbox"/> Test well						
7 Casing: Material Steel Height: above surface Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. Diam. 16 in. to 247 ft. depth Drive shoe? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Weight 36.87 lbs./ft. 1 in. to ft. depth						
8 Screen: Manufacturer Johnson Division Type Galv. Dia. 16" Slot/gauze 201 Length 20' Set between 195 ft. and 205 ft. 220-230 Perfings: 100-195, 205-220, 230-246 Gravel pack <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Size range of material 1/4" down						
9 Static water level: 49 ft. below land surface Date 5-3-75						
10 Pumping level below land surfaces: 75 ft. after 3 hrs. pumping 1280 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1200 g.p.m.						
11 Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date						
12 Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade						
13 Well grouted? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Depth: From 0 ft. to 10 ft.						
14 Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
15 Pump: <input type="checkbox"/> Not installed Manufacturer's name Peerless-FMC Model number 4667 HP 100 Volts Length of drop pipe 140 ft. capacity 1200 g.m.p. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other						
16 Remarks: elevation  Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley						
17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilling Co. 208 Business name <input type="checkbox"/> License No. Address Box 493 Garden City, Ks. Signed <input type="checkbox"/> Date 6-27-75 Authorized representative <input type="checkbox"/>						

*The Professionals* **MINTER-WILSON DRILLING CO.** INCORPORATED

Irrigation  
and Domestic  
Water Systems  
Complete Installation  
and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

Gray County Kindswater By Darrell Faulk March 19, 1975

NE<sub>1/4</sub> sec.20 T.26 R. 28 Static Water Level 60Test # 1 Pivot

Location: Across River At Cimarron, take first Road West  
to Dead End, 1 $\frac{1}{4}$  mile South,  $\frac{1}{4}$  West.

0	6	Fine Sand
6	32	Brown Clay
32	82	Medium to Coarse Gravel (Loose)
82	93	Fine to Medium Sand & Gravel 10% Clay (Loose)
93	143	Fine to Medium Sand & Gravel (Loose)
143	155	Brown Clay, streaks of Gravel 30% (Loose)
155	176	Fine to Medium Sand & Fine Gravel 10% Clay (Loose)
176	192	Brown Sandy Clay
192	207	Fine to Medium Sand & Gravel (Loose)
207	220	Brown Sandy Clay
220	230	Fine to Medium Sand & Gravel with Brown Rock (Loose)
230	246	Fine to Medium Sand & Gravel with Brown Rock (Hard Streak)
246	255	S hale (Hard)