

1 LOCATION OF WATER WELL: County: <u>Graz</u>	Fraction <u>SE 1/4 NW 1/4 NW 1/4</u>	Section Number <u>3</u>	Township Number <u>T 26 S</u>	Range Number <u>R 28</u> <u>W</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>From Cimarron, 1 mile west on Hwy. 50, then 1/2 north</u>					
2 WATER WELL OWNER: <u>Benton Farm + Cattle</u>					
RR#, St. Address, Box # : <u>16906 M. Rd.</u>			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : <u>Cimarron, KS. 67835</u>			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>235</u> ft. ELEVATION: <u>235</u> ft.			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>101</u> ft. below land surface measured on mo/day/yr <u>9-4-03</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: <input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No			
5 TYPE OF BLANK CASING USED:					
1 Steel <input checked="" type="radio"/> PVC 3 RMP (SR) 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded			
Blank casing diameter in. to <u>215</u> ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface <u>18</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR 21</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel		5 Fiberglass 6 Concrete tile <input checked="" type="radio"/> PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut <input checked="" type="radio"/> Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From <u>215</u> ft. to <u>235</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>210</u> ft. to <u>180</u> ft., From <u>190</u> ft. to <u>235</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <input checked="" type="radio"/> Bentonite 4 Other					
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From <u>180</u> ft. to <u>190</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit		7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) <u>To Pasture</u>			
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	10	Brown clay + caliche			
10	118	Med. sand + sandrock			
118	123	White rock			
123	182	Med sand + white rock layers			
182	190	Brown clay			
190	235	Med. sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-4-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 533 This Water Well Record was completed on (mo/day/yr) 9-30-03 under the business name of Jantzen Water Well Repair by (signature) [Signature]