

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Gray</u>	<u>NW 1/4 NW 1/4 NE 1/4</u>	<u>3</u>	T <u>26</u> S	R <u>28</u> EW

Distance and direction from nearest town or city street address of well if located within city?

From Cimarron, 1/2 mile north on Hwy. 23, then 1 mile west on M rd.

2 WATER WELL OWNER:	RR#, St. Address, Box #	Board of Agriculture, Division of Water Resources
Joe Beery	P.O. Box 189	Application Number:
City, State, ZIP Code	Cimarron, Ks. 67835	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	290	
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 147 ft. below land surface measured on mo/day/yr 2-19-04 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: <input checked="" type="radio"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <input type="radio"/> Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/>; If yes, mo/day/yr sample was submitted Water Well Disinfected? <input checked="" type="checkbox"/> Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
<input checked="" type="radio"/> PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 5 in. to 260 ft., Dia			
Casing height above land surface 12 in., weight			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<input checked="" type="radio"/> PVC	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	<input checked="" type="radio"/> Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From 260 ft. to 290 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 24 ft. to 290 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<input checked="" type="radio"/> Bentonite	4 Other
Grout Intervals:	From 4 ft. to 24 ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	To Pasture
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	75	Brown clay + Caliche			
75	80	Med. sand			
80	120	Sandrock + Med. sand layers			
120	160	Med. sand			
160	162	Sandrock			
162	280	Fine sand + brown clay layers			
280	290	Med. sand			
290		Bedrock			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="radio"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-19-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 533 This Water Well Record was completed on (mo/day/yr) 2-1-04 under the business name of Jantzen Water Well Repair by (signature) [Signature]
--