

**CORRECTION(S) TO WATER WELL RECORD (WWC-5)**  
(to rectify lacking or incorrect information)

**Location listed as:**

Section-Township-Range: None Given

Fraction (  $\frac{1}{4}$   $\frac{1}{4}$   $\frac{1}{4}$  ): \_\_\_\_\_

County: Gray

**Location changed to:**

11-265-28W

SE SW NE

**Other changes:** Initial statements: \_\_\_\_\_

Changed to: \_\_\_\_\_

Comments: \_\_\_\_\_

verification method: Well address, city map on internet, and  
Cimarron 1:24,000 topo. map.

initials: DRF date: 11/9/2004

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

## WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction COUNTY: GRAY	1/4	1/4	1/4	Section Number T	Township Number S	Range Number R
---------------------------	--------------------------	-----	-----	-----	---------------------	----------------------	-------------------

Distance and direction from nearest town or city street address of well if located within city?

300 S. MAIN CIMARRON, KS 67835-

2 WATER WELL OWNER: GRAY CO. COURT HOUSE

RR#, St. Address, Box #: PO BOX 487

City, State, ZIP code : CIMARRON, KS 67835-

Board of Agriculture, Division of Water Resources

Application Number: |

3 LOCATE WELL'S LOCATION WITH  
AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL 174 ELEVATION: 0  
Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr 06/24/04  
Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm

Estimated Yield 100 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm

Bore Hole Diameter 14 in. to 174 ft., and in. to 0 ft.

WELL WATER TO BE USED AS: IRRIGATION

Was a chemical/bacteriological sample submitted to department? No ;  
If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC

CASING JOINTS: GLUED

Blank casing diameter 8 in. to 174 ft., Dia in. to 0 ft., Dia in. to 0 ft. "

Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21

TYPE OF SCREEN OR PERFORATION MATERIAL: PVC

SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 89 ft. to 169 ft., From 0 ft. to 0 ft.

From 0 ft. to 0 ft., From 0 ft. to 0 ft.

GRAVEL PACK INTERVALS: From 55 ft. to 174 ft., From 0 ft. to 0 ft.

From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE

Grout Intervals: From 35 ft. to 55 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.

What is the nearest source of possible contamination: NONE

Direction from well?

How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	35				
35	40	05 CLAY 02 FINE SAND			RECEIVED
40	60	10 FINE-MEDSAND 05 CLAY			OCT 27 2004
60	80	05 CLAY 39 SAND ROCK 10 FINE-MEDSAND			
80	100	10 FINE-MEDSAND 05 CLAY			
100	130	05 CLAY 10 FINE-MEDSAND 04 COARSE SAND			
130	150	10 FINE-MEDSAND 04 COARSE SAND 05 CLAY			
150	160	05 CLAY 37 FIN-COAR SAN			
160	170	05 CLAY 07 BLUE SHALE			
170	180	31 SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 06/29/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 08/06/04 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Joe's Well Service*