

County: Gray Fraction SE SE SE SE Sec. 25 T 26 S R 28 E (W)

CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5)

(to rectify lacking or incorrect information)

Owner: Lorraine Nugent

Location was listed as:

Section-Township-Range: 25-26S-28W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): SW

Location changed to:

25-26S-28W

SE SE SE SE

Other changes: Initial statements: _____

Changed to: _____

Comments: Well is 100 ft. North & 100 ft. West of SE corner
of section. Observation well number obs13236se.

Verification method: E-mail communications with KS. Dept. of Agriculture
personnel, who have been monitoring this well, and mapping tool
& aerial photos on KGS website.

initials: ORA date: 10/20/2014

Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726

to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: GRAY SW 1/4 1/4 1/4 25 T 26 S R 28 W

Distance and direction from nearest town or city street address of well if located within city?
 FROM CIMARRON SOUTH ON HIGHWAY 23 - 3 1/2 AND 1/4 EAST

2 WATER WELL OWNER: NUGENT, LORRAINE
 RR#, St. Address, Box #: BOX 452 Board of Agriculture, Division of Water Resources
 City, State, ZIP code: CIMARRON, KS 67835- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1	2	3	4
5	6	7	8
9	10	11	12

4 DEPTH OF COMPLETED WELL 260 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 125 ft. below land surface measured on mo/day/yr 06/25/07
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm

Estimated Yield 0 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm

Bore Hole Diameter 6 in. to 260 ft., and in. to 0 ft.

WELL WATER TO BE USED AS: MONITORING

Was a chemical/bacteriological sample submitted to department? No ;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED
 Blank casing diameter 2 in. to 260 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 30 in., weight 200 lbs/ft. Wall thickness or gauge No. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 200 ft. to 240 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 100 ft. to 260 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE
 Grout Intervals: From 0 ft. to 100 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: NONE
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	01 TOPSOIL 02 FINE SAND			
20	40	02 FINE SAND 32 TAN CLAY			
40	60	10 FINE-MEDSAND			
60	100	37 FIN-COAR SAN 06 SMALL GRAVEL			
100	120	02 FINE SAND 32 TAN CLAY 35 CALACHIE			
120	140	32 TAN CLAY 02 FINE SAND			
140	180	02 FINE SAND 32 TAN CLAY			
180	240	37 FIN-COAR SAN 38 SMAL-MED GRA 33 VERY LOOSE			
240	241	08 ROCK LAYERS			
241	260	07 BLUE SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 06/25/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 08/13/07 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Justin Cret*