

1 LOCATION OF WATER WELL: County: Gray		Fraction SE ¼ NE ¼ NW ¼	Section Number 12	Township Number T 26 S	Range Number R 28 EW																																																																														
Distance and direction from nearest town or city street address of well if located within city? 901 E. Avenue A, Cimarron			Lat. 37.80706 Long. -100.33553																																																																																
2 WATER WELL OWNER: Donald Thurston/T-Bone Travel Plaza RR#, St. Address, Box # City, State, ZIP Code			Box 247 Cimarron, KS 67835 Board of Agriculture, Division of Water Resources Application Number:																																																																																
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center; margin-top: 10px;">N NW X NE SW SE S</div>		4 DEPTH OF COMPLETED WELL 75 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 75 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No✓ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓																																																																																	
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 50 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 50 ft. to 75 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 48 ft. to 75 ft., From ft. to ft.																																																																																			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 48 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet?																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>PLUGGING INTERVALS</th></tr></thead><tbody><tr><td>0</td><td>0.5</td><td>Gravel, Sand, Silt,</td><td></td><td></td><td></td></tr><tr><td>0.5</td><td>5</td><td>Silt, sl. clayey, Lt. Brown</td><td></td><td></td><td></td></tr><tr><td>5</td><td>15</td><td>Silt, as above,</td><td></td><td></td><td></td></tr><tr><td>15</td><td>18</td><td>Clay, v. silty, sl. sandy (vf), Brown to Lt. Brow</td><td></td><td></td><td></td></tr><tr><td>18</td><td>25</td><td>Silt, sl. clayey, Brown</td><td></td><td></td><td></td></tr><tr><td>25</td><td>32</td><td>Clay, v. silty, Brown</td><td></td><td></td><td></td></tr><tr><td>32</td><td>39</td><td>Clay, v. silty, Brown</td><td></td><td></td><td></td></tr><tr><td>39</td><td>45</td><td>Clay, silty, sandy (vf-m), Brown</td><td></td><td></td><td></td></tr><tr><td>45</td><td>52</td><td>Sand, vf-c w/f gravel, Lt. Brown</td><td></td><td></td><td></td></tr><tr><td>52</td><td>60</td><td>Sand, f-c w/f-m gravel, Lt. Brown</td><td></td><td></td><td></td></tr><tr><td>60</td><td>75</td><td>Sand, f-c w/f-m gravel, silty in part, Brown</td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td>MW2R, Flushmount</td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	0.5	Gravel, Sand, Silt,				0.5	5	Silt, sl. clayey, Lt. Brown				5	15	Silt, as above,				15	18	Clay, v. silty, sl. sandy (vf), Brown to Lt. Brow				18	25	Silt, sl. clayey, Brown				25	32	Clay, v. silty, Brown				32	39	Clay, v. silty, Brown				39	45	Clay, silty, sandy (vf-m), Brown				45	52	Sand, vf-c w/f gravel, Lt. Brown				52	60	Sand, f-c w/f-m gravel, Lt. Brown				60	75	Sand, f-c w/f-m gravel, silty in part, Brown									MW2R, Flushmount
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																														
0	0.5	Gravel, Sand, Silt,																																																																																	
0.5	5	Silt, sl. clayey, Lt. Brown																																																																																	
5	15	Silt, as above,																																																																																	
15	18	Clay, v. silty, sl. sandy (vf), Brown to Lt. Brow																																																																																	
18	25	Silt, sl. clayey, Brown																																																																																	
25	32	Clay, v. silty, Brown																																																																																	
32	39	Clay, v. silty, Brown																																																																																	
39	45	Clay, silty, sandy (vf-m), Brown																																																																																	
45	52	Sand, vf-c w/f gravel, Lt. Brown																																																																																	
52	60	Sand, f-c w/f-m gravel, Lt. Brown																																																																																	
60	75	Sand, f-c w/f-m gravel, silty in part, Brown																																																																																	
					MW2R, Flushmount																																																																														
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/21/2012 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7/6/12 under the business name of GeoCore, Inc. by (signature)																																																																																			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																																			