WATER WELL REC	CORD	Form W	WC-5	Division of	of Water Resources App.	No.	
1 LOCATION OF WATER WELL:		Fraction			nber Township No.		
		1/4 nw1/4 nu	14 nw 14			R 28 □E 27W	
Street/Rural Address of Well Location; if unknown, distance & direction					ioning System (GPS)		
from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)		
From Cimarron. 31/4 miles west on River rd.				Longitude: (in decimal degrees)			
y to a dividation by miles desired the					Elevation:		
				Datum:	WGS 84, □ NAD 83,	 □ NAD 27	
2 WATER WELL OWNER: Ernie Massoth				Collection M			
RR#, Street Address, Box #: P.O. Box 27			GPS uni	GPS unit (Make/Model:)			
City, State, ZIP Code Cimarron, Ks. 67835			Digital I	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
	Cimar	ron, KS. 6/83	2	Est. Accuracy	z: ☐ <3 m, ☐ 3-5 m,	☐ 5-15 m, ☐ >15 m	
3 LOCATE WELL			. 10	<u>~</u>	_		
WITH AN "X" IN	4 DEPTH OF C	COMPLETED WELL	L		ft.		
SECTION BOX:	Depth(s) Groundwater Encountered (1)						
N	WELL'S STATIC WATER LEVELtt. below land surface measured on mo/day/yr8/30/19.						
×	Pump test data: Well water wasft. after hours pumping gpm						
NW NE	EST. YIELDgpm. Well water wasft. after hours pumpinggpm						
W E							
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
Other (Specify below)							
Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No							
S If yes, mo/day/yr sample was submitted							
mile	Water well disins	fected? 🔀 Yes 🗌	No				
5 TYPE OF CASING USED: Steel X PVC Other							
CASING JOINTS: St. Glued Clamped Welded Threaded							
Casing diameter							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
□ Steel □ Stainless Steel □ Steel □ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From. 24 ft. to							
From							
6 GROUT MATERIAL: Neat cement Cement grout Sentonite Other							
Grout Intervals: From							
What is the nearest source of possible contamination:							
Septic tank							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							
Direction from well			_	_	weil/gas weil		
FROM TO	LITHOLOG		FROM			LUGGING INTERVALS	
		IC LOG	INOM	TO LITT	IO. LOG (COIL.) OF PI	DOGGING INTERVALS	
	n clay	1			, , , , , , , , , , , , , , , , , , , ,		
15 53 Tan	clay+ calic						
	· Sand + San	brock ledges					
75 80 Tax	1 clay						
80 85 Tai	1 Santy clay						
	sand						
88 98 Ce	mented Sand		ļI				
98 110 Tan							
110 125 Tar	1 Saudy clay	4 mcd. Sand					
	, ,		<u> </u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, a reconstructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) 3/30/14 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No 33 This Water Well Record was completed of the day year							
under the business name	of Jantice	n Water Wel	<i>[</i>	by (signatur	re)	full >	
under the business name of Jantzen Water							
						0, Topeka, Kansas 66612-1367. 1 constructed well. Visit us at	