

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.


Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Gray Fraction SE 1/4 NW 1/4 NW 1/4 NW 1/4 Section Number 11 Township Number T 26 S Range Number R 28 E W

2 WELL OWNER: Last Name: Davis First: Rod Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Pine St. & Ave A 1350' West 920' North then 150' SE

3 LOCATE WELL WITH "X" IN SECTION BOX: N



4 DEPTH OF COMPLETED WELL: 200 ft. Depth(s) Groundwater Encountered: 1) 96 ft. 2) ... ft. 3) ... ft., or 4) Dry Well WELL'S STATIC WATER LEVEL: 96 ft. below land surface, measured on (mo-day-yr) 02/25/2021

5 Latitude: 37.808954 (decimal degrees) Longitude: 100.359079 (decimal degrees) Datum: WGS 84 NAD 83 NAD 27 Source for Latitude/Longitude: GPS (unit make/model: (WAAS enabled? Yes No) Land Survey Topographic Map Online Mapper:

6 Elevation: 2640 ft. Ground Level TOC Source: Land Survey GPS Topographic Map Other KOLAR

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 5. Public Water Supply: well ID 6. Dewatering: how many wells? 7. Aquifer Recharge: well ID 8. Monitoring: well ID 9. Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection 10. Oil Field Water Supply: lease 11. Test Hole: well ID Cased Uncased Geotechnical 12. Geothermal: how many bores? a) Closed Loop Horizontal Vertical b) Open Loop Surface Discharge Inj. of Water 13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 6 in. to 200 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 18 in. Weight lbs./ft. Wall thickness or gauge No. SDR17

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft., From 160 ft. to 200 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 0 ft. to 5 ft., From 60 ft. to 200 ft., From ft. to ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 5 ft. to 60 ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination: No potential source of contamination within 200 ft. Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? N Distance from well? 8 ft.

Table with columns: 10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS

Notes:

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 02/25/2021 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 846 This Water Well Record was completed on (mo-day-year) 03/04/2021 under the business name of Nash Water Well Service, LLC

Form	WWC5
Contractor	Nash Water Well Service, LLC
Well Owner	Rod Davis
Doc ID	1562831

Lithology

From	To	Lithologic Log
0	35	TOP SOIL FINE MEDIUM SAND WITH
		WITH BROWN CLAY
35	80	FINE COARSE SAND WITH SMALL
		GRAVEL WITH TAN CLAY STREAKS
80	90	TAN CLAY CALICHE ROCK & FINE
		MEDIUM SAND
90	100	FINE COARSE SAND WITH BROWN
		& TAN CLAY
100	140	FINE COARSE SAND WITH BROWN CLAY
140	160	TAN BROWN CLAY WITH FINE
		SAND STREAKS & LAYERS
160	190	FINE COARSE SAND WITH SMALL
		GRAVEL
190	203	FINE MEDIUM SAND WITH TAN CLAY
203	206	HARD ROCK LAYER
206	220	BLUE SHALE

RECEIVED
 255 21 5/31
 BUREAU OF WATER