

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: GRAY <i>MW 1</i>	SE 1/4 SE 1/4 NE 1/4	10	T 26 S	R 29 E/W

Distance and direction from nearest town or city street address of well if located within city?

2 miles South of Ingalls Kansas at county Lanfill

2 WATER WELL OWNER:	Gray County	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	915 North Main	Application Number:
City, State, ZIP Code :	Cimarron, Kansas 67835	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 78 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 69 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL . 69 ft. below land surface measured on mo/day/yr . 9/14/93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter . 8 in. to 7.8 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter . 4 in. to 7.8 ft., Dia . in. to ft., Dia . in. to ft.			Threaded . X
Casing height above land surface . 36 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From . 58 ft. to 78 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From . 55 ft. to 78 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From . 1 ft. to 55 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Sewage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Brownish yellow sands	0	55	Voclay Grout
5	15	Brownish yellow sands			
15	30	Sands Medium to Coarse			
30	37	Coarse sands light silts			
37	46	Coarse sands, Some rock			
46	48	Sandy Clays			
48	78	Brown Sands			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/14/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 535 This Water Well Record was completed on (mo/day/yr) 9/14/93 by (signature) James O. Puyear under the business name of Puyear Contractors Inc.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.