


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County GRAY <i>MW 3</i>		Fraction NE $\frac{1}{4}$ SE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 10	Township Number T26 S	Range Number R29 E/W	
Distance and direction from nearest town or city street address of well if located within city? 2 miles South of Ingalls Kansas at county Lanfill						
2 WATER WELL OWNER: Gray County RR#, St. Address, Box #: 915 North Main City, State, ZIP Code: Cimarron, Kansas 67835		Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL. 80 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 69 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 69 ft. below land surface measured on mo/day/yr 9/16/93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 80 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. X Blank casing diameter 4 in. to 80 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 57 ft. to 80 ft., From ft. to ft. From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) SANITARY LANDFILL Direction from well? North & South How many feet?						
FROM 0	TO 24	LITHOLOGIC LOG Brownish yellow sands		FROM 0	TO 57	PLUGGING INTERVALS Voclay Grout
24	27	Silty Clay				
27	35	Sands Fine To Medium				
35	46	Yellow sands light silts				
46	62	Coarse sands, Some rock				
62	80	Wet Sands				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/15/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 535 Puyear Contractors Inc. This Water Well Record was completed on (mo/day/year) 9/16/93 by (signature) James O. Puyear						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						