

CORRECTION(S) TO WATER WELL RECORD (WWC-5)
(to rectify lacking or incorrect information)

County: Gray

Location listed as:

Section-Township-Range: 6-26 S-28 W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): NW NW NW

Location changed to:

1-26 S-29 W

NW NW NW

Other changes: Initial statements:

Changed to:

Comments:

verification method: Written description, city map, and mapping tool & aerial photos on KGS website.

initials: DR date: 1/27/2009

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Gray		Fraction 1/4 NW 1/4 NW 1/4	Section Number 6	Township Number T 26 S	Range Number R 28 E
Distance and direction from nearest town or city street address of well if located within city? Near high school basketball court, Ingalls					
2 WATER WELL OWNER: KDHE RR#, St. Address, Box # : 1000 SW Jackson St., Suite 410 City, State, ZIP Code : Topeka, KS 66612-1367		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 155 ft. ELEVATION: 0 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 47.32 ft. below land surface measured on mo/day/yr 10/20/2004 Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 16.7 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded Threaded. ✓	
Blank casing diameter 4 in. to 135 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 135 ft. to 155 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 45 ft. to 16.7 ft. From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 39.5 ft. From 39.5 ft. to 45 ft. From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? How many feet? 0					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	Sand, fine to coarse, silty, Dark Grayish Brown			
15	45	Sand, fine to coarse, tr. Silt, Brown			
45	55	Sand, fine to coarse, tr. Clay, Brown			
55	65	Sand, fine to coarse, with Clay, Brown			
65	77	Sand, fine, poorly graded, Brown			
77	85	Gravel, sandy, fine, poorly graded, Brown			
85	100	Sand, fine to coarse, clayey, tr. fine gravel, Pal			
100	120	Sand, fine to coarse, tr. clay, Brown			
120	135	Sand, fine to coarse, with Clay, Grayish Brown			
135	145	Sand, fine, w/little Silt, poorly graded, Yellowi			
145	155	Sand, fine to coarse, clayey, Brown			
155	167	Sand, fine to coarse, clayey, Brown			
RECEIVED					
NOV 22 2004					
BUREAU OF WATER					
KDHE Project Code C606971817					
MW5, Flushmount					
Project Name: Golder - Ingalls PWS					
GeoCore # 1184, #					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/11/2004 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 11/5/2004 under the business name of GeoCore, Inc. by (signature) Dale Roll					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

E/M

SEC.