


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Gray	Fraction SE 1/4 NW 1/4 SE 1/4	Section number 11	Township number T 26 S R 29 E	Range number 29
2. Distance and direction from nearest town or city: 1 1/2 south, 3/4 east, 1/4 north of Street address of well location if in city: Ingalls.				3. Owner of well: Jack Wartman R.R. or street: City, state, zip code: Pierceville, Ks. 67868		
4. Locate with "X" in section below: N W E S 1 Mile Sketch map: 				6. Bore hole dia. 26 in. Completion date 5-18-77 Well depth 236 ft.		
5. Type and color of material				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 237 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gauge No. 250		
				10. Screen: Manufacturer's name Johnson Type galv. Dia. 16" Slot/ 1/8" Length 20 ft. Set between 205 ft. and 225 ft. Perf: 90-205 ft. and 225-236 ft. Gravel pack? yes Size range of material 1/2" down		
				11. Static water level: 53 ft. below land surface Date 4-9-77 mo./day/yr.		
(Use a second sheet if needed)				12. Pumping level below land surfaces: 74 ft. after 2 hrs. pumping 1100 g.p.m. 84 ft. after 4 hrs. pumping 1700 g.p.m. Estimated maximum yield 1700 g.p.m.		
				13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date		
				14. Well head completion: 12 inches above grade <input type="checkbox"/> Pitless adapter		
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: N/A ft. Direction Type Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		
18. Elevation: Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley				17. Pump: Not installed Manufacturer's name Goulds - US Pump Model number 12JMO HP 75 Volts Length of drop pipe 140 ft. capacity 1200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilling Co. 208 Business name License No. Address Box A Garden City, Ks. Signed [Signature] Date 7-25 Authorized representative		
				19. Remarks:		

Forward the white, blue and pink copies to the Department of Health and Environment

Professionals

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67841

JACK WARTMAN
GRAY COUNTY
3/9/77

Location: SE 11-26-29 250 Ft. south of pivot

Static Water Level- 45'

Test #3

0	12	Fine sand
12	21	Brown clay
21	51	Fine to med. sand and gravel
51	62	Brown clay
62	84	Fine to med. sand and gravel
84	93	Brown clay
93	117	Fine to med. sand and gravel
117	184	Brown clya
184	229	Fine to med. sand and gravel
229	236	Brown and yellow clay
236	245	shale

T.D. 236