

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Gray	Fraction NW¹/₄ NW¹/₄ NW¹/₄	Section number #23	Township number T #26	Range number S R #29
2. Distance and direction from nearest town or city: 3 miles south of Ingalls, Ks.				3. Owner of well: Clyde Muntz		
Street address of well location if in city:				R.R. or street: City, state, zip code: Ingalls, Kansas 67853		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 5-13-76		
				Well depth 235 ft.		
5. Type and color of material		From	To	7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
Sandy Topsoil		0	15	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Fine sand		15	30	9. Casing: Material RMP Height: Above or below 12 in. Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight 235 lbs./ft. Dia. 5 in. to 235 ft. depth Wall thickness 230 inches or Dia. 5 in. to 235 ft. depth gage No. 230		
Fine sand & clay layers		30	45	10. Screen: Manufacturer's name Sunflower Type RMP Dia. 50 Slot 1/8" Length 20 ft. Set between 210 ft. and 230 ft. ft. and 1/8" ft. Gravel pack <input checked="" type="checkbox"/> Size range of material 4		
Fine sand & clay layers		45	75	11. Static water level: 85 ft. below land surface Date 5-13-76		
Fine to medium sand		75	90	12. Pumping level below land surfaces: 85 ft. after 2 hrs. pumping 50 g.p.m. ft. after 2 hrs. pumping 50 g.p.m. Estimated maximum yield 80 g.p.m.		
Medium to coarse sand		90	105	13. Water sample submitted: 80 mo./day/yr.		
Coarse gravel		105	135	14. Well head completion: 12 inches above grade <input checked="" type="checkbox"/> Pitless adapter 12 inches above grade		
Sand rock		135	150	15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement 20 ft. to 20 ft. Barn Depth: From 7 ft. to 20 ft. Yard		
Sand rock & clay layers		150	165	16. Nearest source of possible contamination: East ft. 150 Direction East Type Yard Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
Clay layers		165	225	17. Pump: Not installed Manufacturer's name Flint & Walling Model number 10BK9 HP 1 Volts 230 Length of drop pipe 147 ft. capacity 19 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
Medium to coarse gravel		225	240	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. JOE'S WELL SERVICE 179 Business name Box 174 Cimarron Ks. license No. Address 6-15-76 Signed Joe I. Cruck Date 6-15-76 Authorized representative		
18. Elevation:		19. Remarks:				
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		(Use a second sheet if needed)				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5