

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Gray		NE 1/4 NE 1/4 NE 1/4		29		T 26 S		R 29	
Distance and direction from nearest town or city street address of well if located within city?									
From In alls, Ks. - 4 miles South and 2 miles West									
2 WATER WELL OWNER: Husky Drilling (Jury)									
RR#, St. Address, Box # : City, State, ZIP Code :									
Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 95 ft. below land surface measured on mo/day/yr 11-26-82 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 75 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 180 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No XXX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XXX No							
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XXX Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 180 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 12 in., weight 200 psi lbs./ft. Wall thickness or gauge No. DR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 140 ft. to 180 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 12 ft. to 180 ft., From ft. to ft. From ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 12 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: none 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG									
0 15 Topsoil & fine sand									
15 30 04 Fine sand & clay									
30 60 01 Clay									
60 75 Clay & medium to coarse sand									
75 135 Coarse sand & brown sandy clay layers									
135 150 04 Coarse sand & white clay									
150 165 09 Coarse sand									
165 180 04 Coarse sand & clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-26-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) August 27, 1983 under the business name of Joe's Well Service, Inc. Cimarron, Ks. by (signature) Long Crick INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									