

WATER WELL RECORD			
Form WWC-5		KSA 82a-1212	
1 LOCATION OF WATER WELL:		Fraction	Section Number Township Number Range Number E/W
County: Sedgwick		SE ¼ SE ¼ SE ¼	10 T 26 S R 3 E/W
Distance and direction from nearest town or city street address of well if located within city?			
501 Andale Road, Andale, KS			
2 WATER WELL OWNER: James Molitor			
RR#, St. Address, Box #: P.O. Box 156		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: Andale, KS		Well # MW-12	Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION: 1426.87	
		Depth(s) Groundwater Encountered 1. 23 ft. 2. ft. 3. ft.	
		WELL'S STATIC WATER LEVEL .21.40 ft. below land surface measured on mo/day/yr 5/15/95	
		Pump test data: Well water was ft. after hours pumping gpm	
		Est. Yield gpm: Well water was ft. after hours pumping gpm	
		Bore Hole Diameter .8 in. to 35 ft., and in. to ft.	
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>(1)</u> Monitoring well	
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted	
		Water Well Disinfected? Yes No	
5 TYPE OF BLANK CASING USED: 1 Steel ② PVC 3 RMP (SR) 4 ABS		Casing Joints: Glued Clamped Welded Threaded	
Blank casing diameter 2 in. to 20 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface -6 in., weight lbs./ft. Wall thickness or gauge No. SCH 40			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel		⑦ PVC 10 Asbestos-cement 8 RMP (SR) 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut ⑧ Saw cut 9 Drilled holes 11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 20 ft. to 35 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 35 ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ③ Bentonite 4 Other			
Grout Intervals: From 1 ft. to 20 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens ⑪ Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)			
Direction from well? Southwest		How many feet? 45	
FROM	TO	LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0	0.5	Concrete	
0.5	2	Sand and gravel fill	
2	14	Brown silty clay	
14	21	Brown and gray silty clay	
21	35	Brown silty clay	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/23/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 534 This Water Well Record was completed on (mo/day/yr) 3/12/96 by (signature) [Signature]			
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.			