

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SE 1/4 SE 1/4	Section Number 36	Township Number T 26 S	Range Number R 3W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

21916 W. 29th N. Wichita, Kansas

WATER WELL OWNER: NEVILLE, Greg	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 21916 W. 29th N.	Application Number:
CITY, STATE, ZIP CODE: Wichita, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 125 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 10/01/1997
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 12 in. to 125 ft. and in. to ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <input checked="" type="checkbox"/> No

5 TYPE OF CASING USED:	5 Wrought iron 8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (Specify below)	Welded
2 PVC 4 ABS	7 Fiberglass	Threaded
Blank casing Diameter 5 in. to 85 ft., Dia in. to ft., Dia in. to ft.	weight 2.35 lbs. / ft.	Wall thickness or gauge No. .214
Casing height above land surface 12 in.,		
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 85 ft. to 125 ft., From ft. to ft.		
GRAVEL PACK INTERVALS: from 24 ft. to 125 ft., From ft. to ft.		

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug	GROUT INTERVALS: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandon water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent	

Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	topsoil			
4	88	clay			
88	95	clay and fine sand			
95	122	shale			
122	125	limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/01/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10/03/97	Under the business name of Harp Well & Pump Service, Inc by (signature) <i>Todd S. Harp</i>
--	--