

1] LOCATION OF WATER WELL: Section Number 8, Township Number 26, Range Number 3. County: Sedgwick. Distance and direction from nearest town or city street address of well if located within city? 6200 N. 27th W.

2] WATER WELL OWNER: Urban EER. RR#, St. Address, Box #: . City, State, ZIP Code: . Board of Agriculture, Division of Water Resources. Application Number: .

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-acre section with an 'X' in the SE corner].

4] DEPTH OF COMPLETED WELL: 111 ft. ELEVATION: 7-16-03 ft. Depth(s) Groundwater Encountered: 35 ft. below land surface measured on mo/day/yr. WELL'S STATIC WATER LEVEL: 35 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 16 gpm, Well water was 11 ft. after 11 hours pumping. Est. Yield: 16 gpm. Well water was 11 ft. after 11 hours pumping. Bore Hole Diameter: 11 in. to 11 in. ft., and 11 in. to 11 in. ft.

5] TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below). CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 5 in. ft., Dia. 2.40 in. to 2.40 in. ft., Dia. 11 in. to 11 in. ft., Dia. Casing height above land surface: 2 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 11.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole).

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 11 None (open hole), 12 Other (specify).

SCREEN-PERFORATED INTERVALS: From 36 ft. to 111 ft., From 111 ft. to 111 ft., From 111 ft. to 111 ft., From 111 ft. to 111 ft.

GRAVEL PACK INTERVALS: From 35 ft. to 111 ft., From 111 ft. to 111 ft., From 111 ft. to 111 ft., From 111 ft. to 111 ft.

6] GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 35 ft. to 35 ft., From 35 ft. to 35 ft., From 35 ft. to 35 ft., From 35 ft. to 35 ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below).

Direction from well? northeast. How many feet? 180.

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 topsoil

2 35 clay

35 111 Charcoal/green shale

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-16-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318. This Water Well Record was completed on (mo/day/yr) 7-21-03 under the business name of Weniger Drilling Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.