WA	TER WE	LL RECORD	Form W	WC-5	Division of Wate	r Resources App. No	0.
		OF WATER WELL:	Fraction	~	Section Number	Township No.	Range Number
			Fraction SE 1/2 NW 1/4		14	T 26 S	R3 DE WW
	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here				Global Positioning		
				k here 📋.	Latitude:		
•	305 Ĵubilee St Andale, KS 67001				Longitude: (in decimal degrees) Elevation:		
				Datum: WGS 84, NAD 83, NAD 27			
2		ELL OWNER: Vision I		Collection Method:			
		Address, Box #: Box 224		GPS unit (Make/Model:)			
	City, State, 2	Colwich : Colwich	i. KS 67030	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL							
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 80						
	SECTION BOX: Depth(s) Groundwater Encountered (1).30 ft. (2)						
	N WELL'S STATIC WATER LEVEL. 30ft. below land surface measured on mo/day/yr						
	Pump test data: Well water wasft. after hours pumpinggpm						
ŀ	EST. YIELD. 18gpm. Well water was						
W							
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
ļ	SW - SE -						
	Was a chemical/bacteriological sample submitted to Department? Yes No						
	S If yes, mo/day/yr sample was submitted						
1		Water well disir	fected? Ves 🗌	No	e d		
5	TYPE OF CASING USED: Steel PVC Other						
CA	CASING JOINTS: Glued Clamped Welded Threaded						
(Casing diameter .5. in. to 80 ft. Diameter in. to ft. Diameter in. to ft. Diameter in. to ft.						
	Casing height above land surface. 12 in., Weight 2.5 lbs./ft., Wall thickness or gauge NoSDR26						
T	TYPE OF SCREEN OR PERFORATION MATERIAL:						
1	Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
Sc	☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:						
"	☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
	☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)						
SCREEN-PERFORATED INTERVALS: From							
From							
GRAVEL PACK INTERVALS: From 20							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From .3							
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)							
☑ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well							
	OM TO	LITHOLOG	IC LOG	FROM			GGING INTERVALS
0	20	Hard Clay		INON	IV DIFIIO. D	oc (conc.) or 1 DO	COMIC MILICANDO
20	55	Soft Sticky Clay					T
55	60	Fine Sand		 			
60	80	Medium to Coarse San	ıd				•
		•					
-							
				<u> </u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☑ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .10/7/2015 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 238 This Water Well Record was completed from mo/day/year 107/2015							
							answers. Send one conv to
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							