		WATER W	ELL RECORI	D For	m WW	/C-5 K	(SA 82a-121	12			
1 LOCATION OF WATE	R WÉLL:	FRACTION			SECT	ION NUMBE	R TOWNSHIP	NUMBER	RANGE N	UMBER	
Sedgwick		NE 1/4	NE 1/4	NE 1/	/4	22	Т 20	6 S	R 3V	V E/W	
Distance and direction fro	m nearest town or cit	ty street address of well	I if located within city?								
25349 W. 53r	****		le, Kansas								
2 WATER WELL		LLER, David						Board of Agri	culture, Division of \	Water Resource	
RR#,ST. ADDRESS			W. 53rd Ct. North					•			
		dale, Kansas		4.5		P CODE:		Application Num	ber:		
3 LOCATE WELL'S LOW		DEPTH OF COMP	PLETED WELL:	45	ft.		ELEVATION:				
N N	D D	epth of groundwater			ft.			ft.	1/1	9/18 ft.	
	\times \mid \vee	VELL'S STATIC WA	ATER LEVEL	22 F7	r. Belo'	W LAND SU	JRFACE MEASL	JRED ON mo/d	lay/yr:		
NW -	NE	Pur	mp test data: \	Well water v	was		ft. after	hours	of pumping @	gpm	
w N		Est. Yield:	J,	Well water v		_	ft. after	hours	of pumping @	gpm	
		Bore Hole Diameter			to 9	5 ft	. and	in.	to	ft.	
Sw -		VELL WATER TO B				7 Lawn	and garden only	9. Dewaterii	9	ection well	
	\$E			ıblic water				10. Monitorir		pecify below	
		Irrigation 4.Was a chemical/bacter		I field wate		YES	nditioning NO		what mo/day/yr	was sample	
S	s	submitted	noogiour sample sabi	mice to Dept	artinone.		Water Well Disint	fected?	YES	NO	
5 TYPE OF CAS	SING USED:	5 111	7 5%		9 Ot	her (Specif	v helow) CAS	ING JOINTS: (Glued	Threaded	
1. Steel	3. RPM (\$	5. Wrought	iron 7. Fib	erglass		R-26	, 20.011,		Welded	Clamped	
2. PVC	> 4. ABS	6. Asbestos	s-Cement 8. Co	ncrete tile	SDI	X-20				,	
Blank casing diamet	er 5	in. to	40 ft., i	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height above	e land surface:	12 in.,	Weig	ght: 2	35 It	os. / ft.	Wall th	ickness or gaug	ge No214	ļ	
TYPE OF SCREEN		•		J					,		
1. Steel	3. Stainless Steel	5. Fiberglass	7. PV	\supset	9. Al	BS	11. Ot	her (specify)			
2. Brass	4. Galvanized	6. Concrete T	ile 8. RM	P (SR)	10. A	sbestos-Ce	ment 12. No	ne used (open	hole)		
SCREEN OR PERFO	ORATION OPENIA	NGS ARE:									
1. Continuous slo			Gauzed wrapped		7. To	rch cut	9. Drill	ed holes	11. None (open hole)	
			* *			w cut			`		
2. Louvered shutte	er 4. Key	punched 6. V	Wire wrapped	,	_	w cut	10. Oth	er (specify)			
SCREEN - PERFORA	ATION INTERVAL	- From	40 ft.	to	95	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL PA	ACK INTERVALS:	From	24 ft.	to	95	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
6 GROUT MATER	IALS: 1 Non	nt cement	2. Cement Gro			Bentonite			onite hole pl		
Grout Intervals:	From 4	ft. to	2. Cement Gro	From	ft.			From	ft. to	_	
What is the nearest s		contamination:	·,			to	ft.,	FIUIII			
1. Septic tank 4. Lateral lines 7. Pit privy 10					Livestoc	k pens	13. Insecti	Insecticide storage 15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Oth							16. Other (s	pecify below)			
3. Watertight sew	erline 6. Seep	page pit 9	Feed yard	12. l	Fertilize	storage					
Direction from well?	Nor						How ma	any feet? 40 f	t. plus		
From To		LITHOLOGIO	CLOG		From	То		LITHOLC	GIC LOG		
0 3	topsoil										
3 20	clay										
20 28	very fine sa	nd				<u> </u>					
28 95	gray shale										
	 						ļ				
	<u> </u>			-			†				
	•									·	
											
	<u> </u>										
			 								
				<u> </u>		<u> </u>					
					·	l	<u> </u>				
7 Contractor's or	Landowner's Cert	ification: This water	well was 1. cons	structed	2. re	constructe	d or 3.	plugged	under my jurisdic	tion and	
was completed on	(mo/day/year)	1/19/18	and this	record is tr	rue to the	best of my	knowledge and l	pelief.			
Kansas Water Wei	, , , ,	onse No. 236				-	d on (mo/day/yea		2/18		
							` ,				
under the business	sname of Har p	Well and Pun	np Service		Dy (Si	gnature)	To	oaa S	. Harp)	