

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sedgewick</u>	<u>SE 1/4 SE 1/4 SE 1/4</u>	<u>10</u>	T <u>26</u> S	R <u>3</u> E <u>W</u>

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>James Molitor</u> <u>501 Andale Rd</u>	Application Number:
City, State, ZIP Code : <u>Andale, KS. 67001</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>40.2</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>28.6</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>28.6</u> ft. below land surface measured on mo/day/yr
	Pump test data. Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter in. to ft. and in. to ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>	
Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <u>No</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement 9 Other (specify below) <u>Welded</u>
<u>2 PVC</u> 4 ABS	7 Fiberglass <u>Threaded</u>
Blank casing diameter <u>2</u> in. to <u>25</u> ft. Dia in. to ft.	
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>7 PVC</u> 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>25</u> ft. to <u>40.2</u> ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>40.5</u> ft. From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From <u>0</u> ft. to <u>21</u> ft. From <u>21</u> ft. to <u>23</u> ft. From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy <u>11 Fuel storage</u> 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	
Direction from well? How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	CONCRETE			
5	4	DARK brown silty sandy clay			
4	6	Brown silty sand clay			
6	12	GREY silty clay			
12	40	RED brown silty clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-29-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>438</u> This Water Well Record was completed on (mo/day/yr) <u>3/24/99</u> under the business name of <u>Kansas City Testing Lab Inc.</u> by (signature) <u>[Signature]</u>
