

1 LOCATION OF WATER WELL County: <u>Adair</u>	Fraction <u>SW 1/4 NE 1/4 SE 1/4</u>	Section Number <u>10</u>	Township Number <u>T 26 S</u>	Range Number <u>R 3 E</u>
--	--------------------------------------	--------------------------	-------------------------------	---------------------------

Distance and direction from nearest town or city street address of well if located within city?

609 Crestview Ct. Andale KS.

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<u>Swellington Const.</u> <u>632 Seville</u> <u>Wichita KS 67209</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>65</u> ft. ELEVATION:
--	---

1 Mile

Depth(s) Groundwater Encountered 1. 44 ft. 2. 44 ft. 3. 44 ft.

WELL'S STATIC WATER LEVEL 44 ft. below land surface measured on mo/day/yr 3-15-83

Pump test data: Well water was 45 ft. after 1/2 hours pumping 20 gpm

Est. Yield 50 gpm: Well water was 45 ft. after 1/2 hours pumping 20 gpm

Bore Hole Diameter: 11 in. to 65 ft., and 65 in. to 65 ft.

WELL WATER TO BE USED AS:

☒ 1 Domestic	☐ 3 Feedlot	☐ 6 Oil field water supply	☐ 9 Dewatering	☐ 12 Other (Specify below)
☐ 2 Irrigation	☐ 4 Industrial	☐ 7 Lawn and garden only	☐ 10 Observation well	

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
------------------------------	----------------	-----------------	---------------------------------------

1 Steel

2 PVC

Blank casing diameter 5 in. to 51 ft., Dia 51 in. to 51 ft., Dia 51 in. to 51 ft.

Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No SDR-26

3 RMP (SR)

4 ABS

7 Fiberglass

8 RMP (SR)

9 ABS

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 51 ft. to 65 ft., From 51 ft. to 65 ft., From 51 ft. to 65 ft.

GRAVEL PACK INTERVALS: From 16 ft. to 65 ft., From 16 ft. to 65 ft., From 16 ft. to 65 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 6 ft. to 16 ft., From 6 ft. to 16 ft., From 6 ft. to 16 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? West

How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top so.			
2	47	Red clay.			
47	65	med sand.			
65	-	shale -			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-15-83</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>4-1-83</u> under the business name of <u>Weninger Swelling</u> by (signature) <u>Weninger Swelling</u>

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

26 R

R

3

RM

SEC.

10

SW 1/4

NE 1/4

SE 1/4

1/4