

1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 NW 1/4 Section 14 Township Number 26 S Range Number 3 E Distance and direction from nearest town or city street address of well if located within city 403 Huntington Andale KS

2 WATER WELL OWNER: RR#, St. Address, Box # : Bx 754 Ordway KS 67052 City, State, ZIP Code Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in SW 1/4]

4 DEPTH OF COMPLETED WELL: ft. ELEVATION: 4-4.85 ft. Depth(s) Groundwater Encountered 1. 29 ft. 2. 29 ft. 3. 20 ft. WELL'S STATIC WATER LEVEL 29 ft. below land surface measured on mo/day/yr Pump test data: Well water was 29 ft. after 12 hours pumping 20 gpm Est. Yield 25 gpm: Well water was 29 ft. after 12 hours pumping 20 gpm Bore Hole Diameter 11 in. to 71 ft. and 71 in. to 71 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter 5 in. to 60 ft. Dia 1.59 in. to 50 ft. Dia Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No 50R-26 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 60 ft. to 71 ft. From 13 ft. to 71 ft. GRAVEL PACK INTERVALS: From 13 ft. to 71 ft. From 13 ft. to 71 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 71 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? North How many feet? 10

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-4-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 4-4-85 under the business name of Weger Duller by (signature) Weger Duller

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.