


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Fraction <u>SE 1/4 NW 1/4 NW 1/4</u> Section Number <u>14</u> Township Number <u>T 26 S</u> Range Number <u>R 3 E</u>					
Distance and direction from nearest town or city street address of well if located within city? <u>See Below</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : <u>Mike Hieger 406 Huntington Rd Andate KS 67001</u> City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>65</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>48</u> ft. 2. <u>48</u> ft. 3. <u>48</u> ft. WELL'S STATIC WATER LEVEL <u>48</u> ft. below land surface measured on mo/day/yr <u>10-12-88</u> Pump test data: Well water was <u>48</u> ft. after <u>12</u> hours pumping <u>20</u> gpm Est. Yield <u>50</u> gpm: Well water was <u>48</u> ft. after <u>12</u> hours pumping <u>20</u> gpm Bore Hole Diameter: <u>11</u> in. to <u>65</u> ft., and <u>65</u> ft. to <u>65</u> ft. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>				
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC Blank casing diameter <u>5</u> in. to <u>54</u> ft., Dia <u>12</u> in. to <u>1159</u> lbs./ft. Wall thickness or gauge No. <u>SAR 26</u> Casing height above land surface <u>12</u> in., weight <u>1159</u> lbs./ft. 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued <u>X</u> Clamped <u>X</u> Welded <u>X</u> Threaded <u>X</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Stainless steel 4 Galvanized steel 3 Mill slot 4 Key punched 5 Fiberglass 6 Concrete tile 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 7 PVC 8 RMP (SR) 9 ABS 8 Saw cut 9 Drilled holes 10 Other (specify) 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN-PERFORATED INTERVALS: From <u>54</u> ft. to <u>65</u> ft., From <u>65</u> ft. to <u>65</u> ft. GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>65</u> ft., From <u>65</u> ft. to <u>65</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>23</u> ft., From <u>23</u> ft. to <u>65</u> ft., From <u>65</u> ft. to <u>65</u> ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? <u>North</u> How many feet? <u>30</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top so.			
2	48	clay			
48	65	med SAND			
65	-	SHALE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>10-12-88</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>10-12-88</u> under the business name of <u>Waninger Dully</u> by (signature) <u>[Signature]</u>					