

1 LOCATION OF WATER WELL: Fraction SW 1/4 NE 1/4 NE 1/4 Section Number 15 Township Number T 26 S Range Number R 3 E
 County: Sedgewick

Distance and direction from nearest town or city street address of well if located within city?

318 Anderson Road, KS

2 WATER WELL OWNER:

RR#, St. Address, Box # :


City, State, ZIP Code :

Roman Hein
318 Anderson
Andale, KS 67101

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 56 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 29 ft. 2. 29 ft. 3. 29 ft.

WELL'S STATIC WATER LEVEL 29 ft. below land surface measured on mo/day/yr 11-16-82

Pump test data: Well water was 35 ft. after 1/2 hours pumping 15 gpm

Est. Yield 15-20 gpm: Well water was 35 ft. after 1/2 hours pumping 15 gpm

Bore Hole Diameter 11 in. to 56 ft., and 56 in. to 56 ft.

WELL WATER TO BE USED AS:

- 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued X Clamped X

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded X

2 PVC

4 ABS

7 Fiberglass

Threaded X

Blank casing diameter 5 in. to 36 ft., Dia 36 in. to 56 ft., Dia 56 in. to 56 ft.

Casing height above land surface 12 in., weight 159 lbs./ft. Wall thickness or gauge No SPR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 36 ft. to 56 ft., From 56 ft. to 56 ft., From 56 ft. to 56 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 56 ft., From 56 ft. to 56 ft., From 56 ft. to 56 ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 56 ft., From 56 ft. to 56 ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

North

How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top So. /			
2	27	red clay			
27	34	fine sand			
34	35	red clay			
35	56	fine & med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-16-82 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 12-1-82

under the business name of Wenger Dilling by (signature) James Wenger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

26

R

3

EW

SEC.

15

SW 1/4

NE 1/4

NE 1/4