

1 LOCATION OF WATER WELL: County: Sedgewick Fraction: SW 1/4 NE 1/4 NE 1/4 Section Number: 15 Township Number: T 26 S Range Number: R 3 E

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Madelaine Gresh
RR#, St. Address, Box #: 212 Dale
City, State, ZIP Code: Andale KS 67001

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 35 ft.

Depth(s) Groundwater Encountered 1. 35 ft. 2. 40 ft. 3. 42 ft.

WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr 7-2-83

Pump test data: Well water was 40 ft. after 1/2 hours pumping 10 gpm

Est. Yield 15 gpm: Well water was 40 ft. after 1/2 hours pumping 10 gpm

Bore Hole Diameter 1 1/2 in. to 65 ft. and 65 in. to 65 ft.

WELL WATER TO BE USED AS:

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

7 Fiberglass Threaded

Blank casing diameter 5 in. to 45 ft., Dia. 45 in. to 45 ft., Dia. 45 in. to 45 ft.

Casing height above land surface 1.2 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SOR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft., From 45 ft. to 65 ft., From 45 ft. to 65 ft.

GRAVEL PACK INTERVALS: From 13 ft. to 65 ft., From 13 ft. to 65 ft., From 13 ft. to 65 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 13 ft., From 13 ft. to 13 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? SW How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top 50. 1.			
2	45	gray clay.			
45	55	med SAND.			
55	65	Blue green shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-2-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-3-83 under the business name of Weninger Mullen by (signature) James Weninger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T 26 R 3

EWD

SEC.

15

SW 1/4 NE 1/4 NE 1/4