

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NW 1/4 Section Number 22 Township Number T 26 S Range Number R 3 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?
1 So 2/3 West Andale Kansas

2 WATER WELL OWNER: Greg Schmitz
 RR#, St. Address, Box #: 203 W. Anderson
 City, State, ZIP Code: Andale KS 67001
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N				

4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: 22 ft. below land surface measured on mo/day/yr 11-12-81
 Depth(s) Groundwater Encountered 1. 22 ft. 2. 40 ft. 3. 10 ft.
 WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 11-12-81
 Pump test data: Well water was 40 ft. after 12 hours pumping 10 gpm
 Est. Yield 15-25 gpm: Well water was 40 ft. after 12 hours pumping 10 gpm
 Bore Hole Diameter 1 1/2 in. to 95 ft., and 95 in. to 95 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel ☐ 3 RMP (SR) ☒ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued X Clamped X
 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded
 Blank casing diameter 5 in. to 21 ft., Dia. 1.59 lbs./ft. Wall thickness or gauge No. SDR-26
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 7 PVC ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☒ 11 Other (specify) None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☒ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 10 Other (specify) None used (open hole)
 SCREEN-PERFORATED INTERVALS: From 21 ft. to 95 ft. From 21 ft. to 95 ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 95 ft. From 10 ft. to 95 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
 Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 95 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? SW How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	43	Red clay.			
43	46	Blue-green shale			
46	72	GRAY clay.			
72	95	Charcoal shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-12-81 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 11-12-81
 under the business name of Weninger Drilling by (signature) Greg Schmitz
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

26

R

3

EW

SEC. 22

NW 1/4 NE 1/4 NW 1/4