

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>	<u>SW 1/4 SE 1/4 SW 1/4</u>	<u>23</u>	T <u>24</u> S	R <u>3</u> <u>SW</u>

Distance and direction from nearest town or city street address of well if located within city?

See Below

2 WATER WELL OWNER: <u>Mark Gorges</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>RR# 24210 W. 45th N.</u>	Application Number:
City, State, ZIP Code: <u>Andale, KS 67001</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered <u>10</u> ft. 2. <u>10</u> ft. 3. <u>80</u> ft. WELL'S STATIC WATER LEVEL <u>10</u> ft. below land surface measured on mo/day/yr <u>8-17-94</u> Pump test data: Well water was <u>20</u> ft. after <u>1/2</u> hours pumping <u>20</u> gpm Est. Yield <u>30</u> gpm: Well water was <u>20</u> ft. after <u>1/2</u> hours pumping <u>20</u> gpm Bore Hole Diameter <u>11</u> in. to <u>90</u> ft., and <u>90</u> in. to <u>90</u> ft. WELL WATER TO BE USED AS: ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>5</u> in. to <u>30</u> ft., Dia	in. to <u>30</u> ft., Dia	in. to <u>30</u> ft., Dia	in. to <u>30</u> ft., Dia
Casing height above land surface <u>12</u> in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>100 PSI</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 Other (specify)
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel	7 Torch cut	10 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<u>3 Mill slot</u>	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From <u>30</u> ft. to <u>80</u> ft., From <u>30</u> ft. to <u>80</u> ft., From <u>30</u> ft. to <u>80</u> ft., From <u>30</u> ft. to <u>80</u> ft.			
GRAVEL PACK INTERVALS: From <u>10</u> ft. to <u>80</u> ft., From <u>10</u> ft. to <u>80</u> ft., From <u>10</u> ft. to <u>80</u> ft., From <u>10</u> ft. to <u>80</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	<u>2 Cement grout</u>	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>10</u> ft., From <u>10</u> ft. to <u>80</u> ft., From <u>10</u> ft. to <u>80</u> ft., From <u>10</u> ft. to <u>80</u> ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	<u>8 Sewage lagoon</u>	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? <u>Northeast</u>				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>Top Soil</u>			
<u>2</u>	<u>48</u>	<u>Clay</u>			
<u>48</u>	<u>80</u>	<u>Shale</u>			

7 CONTRACTOR'S OR LAND OWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , <u>(2) reconstructed</u> , or <u>(3) plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>8-17-94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>8-19-94</u> under the business name of <u>Weninger Drilling</u> by (signature) <u>Karina Morrisey</u>
--