

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK 087		SW 1/4 NE 1/4 NE 1/4	15	T 26 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city?					
in town MW2					
2 WATER WELL OWNER: SEDGWICK - ANDALE YARD					
RR#, St. Address, Box #: 248 S. MAIN					
City, State, ZIP Code: ANDALE, KS.					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 55.25 ft. ELEVATION:			
		Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL: 44.59 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No ☐			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded					
Blank casing diameter: 2 in. to 40.0 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface: 0 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 40.0 ft. to 55.0 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 37.5 ft. to 55.25 ft., From ft. to ft.					
From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout					
Grout Intervals: From 0 ft. to 1.0 ft. From 1.0 ft. to 34.5 ft. From 34.5 ft. to 37.5 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	1	TOPSOIL ORGANIC FILL			
1	20	CLAY SANDY (F-M) GREY/BLACK			
20	29.0	CLAY SANDY (F-M) BROWN silty			
29	33.0	SANDY (F-M) silty BROWN			
33	55.25	SAND F-M SOME GRAVEL SOME Silty BROWN			
		water at 46.0			
		GREY SHALE HARD BELOW			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-19-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 9/19/94 under the business name of TEST by (signature) Clay P. Dyer					