


1 LOCATION OF WATER WELL: County: SEDGWICK 087	Fraction SW 1/4 NE 1/4 NE 1/4	Section Number 15	Township Number T 26 S	Range Number R 3 EW
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

in town

2 WATER WELL OWNER: RR#, St. Address, Box # : 248 S. MAIN City, State, ZIP Code : ANDALE, KS.	SEDGWICK-ANDALE YARD MW3	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL. 54.25 ft. ELEVATION:
--	--

	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
	WELL'S STATIC WATER LEVEL 43.10 ft. below land surface measured on mo/day/yr			
	Pump test data: Well water was ft. after hours pumping gpm			
	Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter in. to ft., and in. to ft.	WELL WATER TO BE USED AS:			
1 Domestic	5 Public water supply	8 Air conditioning	11 Injection well	
2 Irrigation	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
4 Industrial	7 Lawn and garden only	10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted				
Water Well Disinfected? Yes. No.				

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded

Blank casing diameter 2 in. to 39.0 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)
2 Brass	9 ABS	12 None used (open hole)
3 Stainless steel		
4 Galvanized steel		
5 Fiberglass		
6 Concrete tile		

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			

SCREEN-PERFORATED INTERVALS:	From 39.0 ft. to 54.0 ft., From ft. to ft.
GRAVEL PACK INTERVALS:	From 36.9 ft. to 54.25 ft., From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 1.0 ft., From 1.0 ft. to 33.5 ft., From 33.5 ft. to 36.9 ft.			

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1'	TOPSOIL BLACK ORGANIC			
1	7'	CLAY BROWN SANDY (F-M)			
7	30'	CLAY, REDDISH BROWN, SANDY Silty			
30	45'	SANDY, Silty, BROWN (F-M)			
45	55'	SAND (F-C) w/ GRAVEL			
		WEF AT 44.5			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-20-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 9/1/94 under the business name of TEST by (signature) Clay P. Oyer
