


1 LOCATION OF WATER WELL: County: SEDGWICK 887 Fraction: SW 1/4 NE 1/4 NE 1/4 Section Number: 15 Township Number: T 26 S Range Number: R 3 E EW
Distance and direction from nearest town or city street address of well if located within city? in town

2 WATER WELL OWNER: SEDGWICK-ANDALE YARD RR#, St. Address, Box #: 249 S. MAIN City, State, ZIP Code: ANDALE, KS. Board of Agriculture, Division of Water Resources Application Number: MW7

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 55.75 ft. ELEVATION: 44.22 ft. below land surface measured on mo/day/yr

Depth(s) Groundwater Encountered: 1. 44.22 ft. 2. 44.22 ft. 3. 44.22 ft.
WELL'S STATIC WATER LEVEL: 44.22 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 44.22 ft. after 44.22 hours pumping 44.22 gpm
Est. Yield 44.22 gpm: Well water was 44.22 ft. after 44.22 hours pumping 44.22 gpm
Bore Hole Diameter: 44.22 in. to 44.22 ft., and 44.22 in. to 44.22 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes 44.22; If yes, mo/day/yr sample was submitted 44.22
Water Well Disinfected? Yes 44.22

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 44.22 Clamped 44.22
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 44.22
Blank casing diameter 44.22 in. to 44.22 ft., Dia 44.22 in. to 44.22 ft., Dia 44.22 in. to 44.22 ft.
Casing height above land surface 44.22 in., weight 44.22 lbs./ft. Wall thickness or gauge No. 44.22
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 44.22
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 44.22
7 Torch cut
SCREEN-PERFORATED INTERVALS: From 44.22 ft. to 44.22 ft. From 44.22 ft. to 44.22 ft.
GRAVEL PACK INTERVALS: From 44.22 ft. to 44.22 ft. From 44.22 ft. to 44.22 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 44.22 ft. to 44.22 ft. From 44.22 ft. to 44.22 ft. From 44.22 ft. to 44.22 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? 44.22 How many feet? 44.22

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	GRAVEL PARKING LOT FILL			
1.5	3.0	TOPSOIL FILL BLACK ORGANIC			
3.0	13.0	CLAY, BROWN, SANDY (F-M)			
13.0	30.0	CLAY RED/BROWN SANDY F-M silty			
30.0	33.0	SAND F-M BROWN Silty			
33.0	55.75	SAND F-C w/GRAVEL & SOME silt, BROWN			
		Moist at 42.0			
		Wet at 46.0			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-22-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 9/1/94 under the business name of TEST by (signature) Clay P. Dyer

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.