

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 SE 1/4 SW 1/4	Section Number 3	Township Number T 26 S	Range Number R 3W E/W																																																						
Distance and direction from nearest town or city street address of well if located within city? 1 mile North and 1/2 West of Andale Andale, Kansas																																																										
2 WATER WELL OWNER: CITY OF ANDALE RR#, ST. ADDRESS, BOX #: P.O. Box 338 CITY, STATE, ZIP CODE: Andale, Kansas 67001 Board of Agriculture, Division of Water Resource Application Number:																																																										
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 101 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 35 '1" FT. BELOW LAND SURFACE MEASURED ON 04/15/1995 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 101 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well test well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No																																																									
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded Blank casing Diameter 5 in. to 76 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 76 ft. to 101 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 20 ft. to 101 ft., From ft. to ft. from ft. to ft., From ft. to ft.																																																										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?																																																										
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:10%;">FROM</th> <th style="width:10%;">TO</th> <th style="width:40%;">LITHOLOGIC LOG</th> <th style="width:10%;">FROM</th> <th style="width:10%;">TO</th> <th style="width:20%;">PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>3</td> <td>soil</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>35</td> <td>tan clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>35</td> <td>40</td> <td>sandy tan clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>40</td> <td>50</td> <td>fine clayey sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td>50</td> <td>60</td> <td>fine to coarse sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td>60</td> <td>70</td> <td>medium sand and fine gravel (tan slightly tight)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>70</td> <td>101</td> <td>medium to medium coarse sand and gravel (tan-medium loose)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>101</td> <td>103</td> <td>gray green shale</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>					FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	3	soil				3	35	tan clay				35	40	sandy tan clay				40	50	fine clayey sand				50	60	fine to coarse sand				60	70	medium sand and fine gravel (tan slightly tight)				70	101	medium to medium coarse sand and gravel (tan-medium loose)				101	103	gray green shale			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																					
0	3	soil																																																								
3	35	tan clay																																																								
35	40	sandy tan clay																																																								
40	50	fine clayey sand																																																								
50	60	fine to coarse sand																																																								
60	70	medium sand and fine gravel (tan slightly tight)																																																								
70	101	medium to medium coarse sand and gravel (tan-medium loose)																																																								
101	103	gray green shale																																																								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/15/1995 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 05/01/95 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>																																																										