


County Gray County		Fraction 1/4 SE 1/4 NE 1/4	Section number 1	Township number 26	Range number 30
Location of well: on Hiway 50, 2 1/2 South, 1/4 East		Owner of well: Don Renick R.R. or street: Ingalls, KS 67853 City, state, zip code: #772			
Distance and direction from nearest town or city: 1 East of Charleston		Street address of well location if in city:			
Locate with "X" in section below: 		Sketch map:		6. Bore hole dia. 26 in. Completion date 12-29-78 Well depth 236 ft.	
5. Type and color of material		From		To	
				8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
				9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia 16 in. to 236 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. .219	
				10. Screen: Manufacturer's name Johnson Type Johnson Screen 100-16" Slot/gauze 0-100 Plain 100-120 Perf. Set between 120-130 Screen 130-140 ft. 140-213 Perf. 213-236 Perf. ft. Gravel pack? yes Size range of material: 3/4 to 5/8	
				11. Static water level: <input type="checkbox"/> mo./day/yr. 70 ft. below land surface Date 10-31-78	
				12. Pumping level below land surfaces: 101 ft. after 2 hrs. pumping 1250 g.p.m. 111 ft. after 4 hrs. pumping 1700 g.p.m. Estimated maximum yield 1700 g.p.m.	
				13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	
				14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. Inches above grade	
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
				16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
				17. Pump: Manufacturer's name Gould 4 stg. 12" Bowl Not installed Model number <input type="checkbox"/> HP <input type="checkbox"/> Volts <input type="checkbox"/> Length of drop pipe 140 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter-Wilson Drilling Co. 208 Business name License No. Box A, Garden City, KS 67846 Address Signed [Signature] Date 12/29/78 Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

September 13, 1978

Don Renick
Gray County

Location: N. E. $\frac{1}{4}$ 1-26-30 30 feet East of Pivot
Static Water Level
Test #2

0	1	Top Soil
1	32	Fine Sand
32	42	Brown Clay
42	49	Med. Coarse Gravel (loose)
49	89	Brown Sandy Clay
89	101	Fine to med. sand and gravel
101	107	Brown Clay
107	132	Fine to med. sand and gravel White Rock mixed Loose
132	140	Brown Sandy Clay
140	153	Fine to med. Sand and gravel (loose)
153	171	Brownish Clay
171	179	Fine to med. Sand and fine Gravel (loose)
179	213	Brown Clay
213	234	Fine to med. sand and gravel mixed with yellow Rock (loose)
234	237	Yellow Clay
237	239	Shale (hard)

T. D. 236