

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Gray	Fraction SE 1/4 SE 1/4 SE 1/4	Section number #24	Township number T #26 S R #30	Range number E/W
2. Distance and direction from nearest town or city: 3 mile south, 4 west of Ingalls, Kansas Street address of well location if in city:			3. Owner of well: W. E. Bogerd R.R. or street: City, state, zip code: Cimarron, Kansas 67835			
4. Locate with "X" in section below: N W E S 1 Mile		Sketch map: WELL SHED		6. Bore hole dia. 8 in. Completion date 5-10-76 Well depth 165 ft.		
5. Type and color of material		From	To	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
Sandy Topsoil		0	15	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input checked="" type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Fine sand & clay mixed		15	30	9. Casing: Material RMP Height: Above or below XXXX Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 12 in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight <input type="checkbox"/> lbs./ft. Dia. 5 in. to 165 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 250		
Fine sand & clay layers		30	45	10. Screen: Manufacturer's name Sunflower Type RMP Dia. 5" Slot XXXX 1/8" Length 20 ft. Set between 140 ft. and 160 ft. ft. and 1/2 ft. Gravel pack? yes Size range of material 4		
Fine sand		45	60	11. Static water level: 62 ft. below land surface Date 5-10-76		
Medium to coarse gravel		60	105	12. Pumping level below land surfaces: 65 ft. after 2 hrs. pumping 40 g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 60 g.p.m.		
Coarse gravel		105	120	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/> mo./day/yr.		
Coarse gravel & clay		120	135	14. Well head completion: None <input type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade		
Coarse gravel		135	150	15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 5 ft. to 15 ft.		
Coarse gravel & clay		150	165	16. Nearest source of possible contamination: None ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
(Use a second sheet if needed)				17. Pump: Manufacturer's name Flint & Walling Not installed Model number 7BAT2 HP 3/4 Volts 230 Length of drop pipe 105 ft. capacity 10 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. JOE'S WELL SERVICE 179 Business name Box 174 Cimarron, Ks. License No. 6-15- Address Larry L. Crick Date 6-15-76 Signed Larry L. Crick Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5