


USE TYPEWRITER OR BALL
POINT PEN-RE-SS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County GRAY	Fraction SE 1/4 NW 1/4 SE 1/4	Section number 25	Township number T 26 S	Range number R 30
2. Distance and direction from nearest town or city: 8 south, 1 east 1/2 north, 1/2 west of Charleston Street address of well location if in city:			3. Owner of well: Carolyn Crotts R.R. or street: %Louis Beery City, state, zip code: Cimarron, KS 67846			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 26 in. Completion date 10-14-76 Well depth 232 ft.		
				7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
				8. Use: Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other <input type="checkbox"/>		
5. Type and color of material		From		To		9. Casing: Material steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP 16 PVC 233 Weight 36.85 lb./ft. Dia. 16 in. to 233 ft. depth Wall Thickness: inches or Dia. 16 in. to 233 ft. depth gage No. 232
						10. Screen Manufacturer's name Johnson Screen Type Galv. Dia. 16" Slot/gauze 200 Length 20' Set between 200 ft. and 220 ft. Perf: 100200 ft. and 220-232 ft. Gravel pack? yes Size range of material 1/2" Down
						11. Static water level: 17 ft. below land surface Date 9-27-76
						12. Pumping level below land surfaces: 115 ft. after 3 hrs. pumping 1500 g.p.m. ft. after 3 hrs. pumping 1500 g.p.m. Estimated maximum yield 1500 g.p.m.
						13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date 9-27-76
						14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade
						15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: N/A ft. Field Direction Field Type Field Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
						17. Pump: Not installed Manufacturer's name Goulds US Pump Model number 12JHC HP 100 Volts 100 Length of drop pipe 160 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling 208 Business name P.O. Box A Garden City, KS License No. 9-27-76 Address P.O. Box A Garden City, KS Date 9-27-76 Signature [Signature] Authorized representative
18. Elevation:		19. Remarks:				
Topography: <input checked="" type="checkbox"/> Hill <input type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

the
Professionals

MINTER-WILSON DRILLING CO.
INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

CAROLYN CROTTS
LEWIS BARRY Tenatn
GRAY COUNTY
9-11-76

Location: SE 1/4 25-26-30 offset 300 south of pivot
Static Water Level- 76

Test #A

0	1	Top soil
1	6	Fine sand
6	16	Brown sandy clay
16	55	Fine sand loose
55	59	Fine to med. sand
59	63	Brown sandy clay
63	80	Fine to med. sand and gravel Loose
80	89	Fine to med. sand and gravel some coarse gravel Loose
89	103	Brown ish sandy clay
103	123	Fine to med. sand
123	136	Light brown sandy clay
136	143	Fine to med. sand
143	151	Cemented sandstone mixed white yellow rock hard
151	169	Fine to med. sand and gravel mixed white yellow rock loose
169	178	Brown sandy clay
178	191	Fine to med. sand and gravel Loose
191	202	Brown sandy clay
202	212	Fine to med. sand and gravel
212	232	Fine to med. sand and gravel mixed white yellow rock Loose
232	250	Brown yellow mixed
250	255	Shale