

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL	Fraction NW 1/4 NW 1/4 NW 1/4	Section Number 26	Township Number T 26 ^W S	Range Number R 30 EW
--------------------------	----------------------------------	----------------------	--	-------------------------

Distance and direction from nearest town or city? 6 1/2 miles South of
Charleston and 3 1/4 West Street address of well if located within city?

2 WATER WELL OWNER: Dorothy Bates
RR#, St. Address, Box #: (Herman Frank Well)
City, State, ZIP Code: Moundridge, Kansas 67107

Board of Agriculture, Division of Water Resources
Application Number:

3 DEPTH OF COMPLETED WELL 319 ft. Bore Hole Diameter 8 in. to ft., and in. to ft.

Well Water to be used as: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Well's static water level 128 ft. below land surface measured on Sept. month 11 day 1980 year

Pump Test Data: Well water was 15 ft. after 1 1/2 hours pumping. 15 gpm

Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile Casing Joints: Glued Welded Clamped Threaded

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing dia 5 in. to 412 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No 205 Jet stream

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

Screen or Perforation Openings Are: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .

Screen-Perforation Dia 1.8 in. to xx ft., Dia in. to ft., Dia in. to ft.

Screen-Perforated Intervals: From 187 ft. to 207 ft., From ft. to ft. ft. to ft.

From ft. to ft., From ft. to ft. ft. to ft.

Gravel Pack Intervals: From 20 ft. to 312 ft., From ft. to ft. ft. to ft.

From ft. to ft., From ft. to ft. ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grouted Intervals: From 7 ft. to 30 ft., From ft. to ft., From ft. to ft. ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well

2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well

3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)

Direction from well Northwest How many feet 105 ? Water Well Disinfected? Yes NO No NO

Was a chemical/bacteriological sample submitted to Department? Yes NO If yes, date sample

was submitted month day year Pump Installed? Yes NO No NO

If Yes: Pump Manufacturer's name Goulds Model No. 108J10 HP 1 Volts 230

Depth of Pump Intake 218 ft. Pumps Capacity rated at 10 gal./min.

Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on Sept. month 15 day 1980 year

and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179

This Water Well Record was completed on Nov. month 1 day 1980 year under the business

name of JOHN'S WELL SERVICE, Cimarron, Kansas 67825 by (signature) John P. Crick

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	Top soil & fine sand	210	225	Medium sand
15	75	Fine sand	225	240	Medium to fine sand & clay
75	90	Fine sand to medium sand	240	255	Clay layers & Fine sand
90	105	Medium to coarse sand	255	270	Clay layers & fine sand
105	120	Clay layer to fine to medium sand	270	285	and medium sand
120	135	Medium to coarse sand	285	300	Medium sand
135	150	Coarse sand clay	300	315	Medium sand & Coarse sand
150	165	Clay layers & fine sand			
165	180	Fine sand & clay			
180	195	Clay to fine & medium sand			
195	210	Fine to medium sand			

ELEVATION: 195 ft. 210 ft. 225 ft. 240 ft. 255 ft. 270 ft. 285 ft. 300 ft. 315 ft.

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY