

1 LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number					
County: <u>Gray</u>		<u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$		<u>30</u>		<u>T</u> <u>26</u> <u>S</u>		<u>R</u> <u>30</u> <u>EW</u>					
Distance and direction from nearest town or city? <u>6 miles South of Charleston, Kansas & 1/2 miles West</u>					Street address of well if located within city?								
2 WATER WELL OWNER: <u>Gilbert Rundell</u>													
RR#, St. Address, Box # :					Board of Agriculture, Division of Water Resources								
City, State, ZIP Code : <u>Pierceville, Kansas 67868</u>					Application Number:								
3 DEPTH OF COMPLETED WELL: <u>156</u> ft. Bore Hole Diameter: <u>8</u> in. to ft., and in. to ft.													
Well Water to be used as:													
<u>1 Domestic</u>		<u>3 Feedlot</u>		<u>5 Public water supply</u>		<u>8 Air conditioning</u>		<u>11 Injection well</u>					
<u>2 Irrigation</u>		<u>4 Industrial</u>		<u>6 Oil field water supply</u>		<u>9 Dewatering</u>		<u>12 Other (Specify below)</u>					
<u>7 Lawn and garden only</u>		<u>10 Observation well</u>											
Well's static water level: <u>100</u> ft. below land surface measured on <u>Sept.</u> month <u>3</u> day <u>1980</u> year													
Pump Test Data: Well water was ft. after hours pumping gpm													
Est. Yield <u>30</u> gpm: Well water was ft. after hours pumping gpm													
4 TYPE OF BLANK CASING USED:													
<u>1 Steel</u>		<u>3 RMP (SR)</u>		<u>5 Wrought iron</u>		<u>8 Concrete tile</u>		Casing Joints: <u>Glued</u> <u>Clamped</u>					
<u>2 PVC</u>		<u>4 ABS</u>		<u>6 Asbestos-Cement</u>		<u>9 Other (specify below)</u>		<u>Welded</u>					
<u>3 PVC</u>				<u>7 Fiberglass</u>				<u>Threaded</u>					
Blank casing dia. <u>5</u> in. to <u>156</u> ft., Dia. in. to ft., Dia. in. to ft.													
Casing height above land surface: <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>205</u> Jet stream.													
TYPE OF SCREEN OR PERFORATION MATERIAL:													
<u>1 Steel</u>		<u>3 Stainless steel</u>		<u>5 Fiberglass</u>		<u>8 RMP (SR)</u>		<u>10 Asbestos-cement</u>					
<u>2 Brass</u>		<u>4 Galvanized steel</u>		<u>6 Concrete tile</u>		<u>9 ABS</u>		<u>11 Other (specify)</u>					
<u>12 None used (open hole)</u>													
Screen or Perforation Openings Are:													
<u>1 Continuous slot</u>		<u>3 Mill slot</u>		<u>5 Gauzed wrapped</u>		<u>8 Saw cut</u>		<u>11 None (open hole)</u>					
<u>2 Louvered shutter</u>		<u>4 Key punched</u>		<u>6 Wire wrapped</u>		<u>9 Drilled holes</u>							
<u>7 Torch cut</u>		<u>10 Other (specify)</u>											
Screen-Perforation Dia. <u>1/8</u> in. to <u>20</u> ft., Dia. in. to ft., Dia. in. to ft.													
Screen-Perforated Intervals: From <u>131</u> ft. to <u>151</u> ft., From ft. to ft., From ft. to ft.													
Gravel Pack Intervals: From <u>20</u> ft. to <u>156</u> ft., From ft. to ft., From ft. to ft.													
5 GROUT MATERIAL:													
<u>1 Neat cement</u>		<u>2 Cement grout</u>		<u>3 Bentonite</u>		<u>4 Other</u>							
Grouted Intervals: From <u>15</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.													
What is the nearest source of possible contamination:													
<u>1 Septic tank</u>		<u>4 Cess pool</u>		<u>7 Sewage lagoon</u>		<u>10 Fuel storage</u>		<u>14 Abandoned water well</u>					
<u>2 Sewer lines</u>		<u>5 Seepage pit</u>		<u>8 Feed yard</u>		<u>11 Fertilizer storage</u>		<u>15 Oil well/Gas well</u>					
<u>3 Lateral lines</u>		<u>6 Pit privy</u>		<u>9 Livestock pens</u>		<u>12 Insecticide storage</u>		<u>16 Other (specify below)</u>					
<u>13 Watertight sewer lines</u>													
Direction from well: <u>Northwest</u> How many feet: <u>130</u> ? Water Well Disinfected? Yes <u>XXXX</u> No													
Was a chemical/bacteriological sample submitted to Department? Yes <u>XXXX</u> No <u>XXXX</u> If yes, date sample was submitted month day year Pump Installed? Yes <u>XXXX</u> No													
If Yes: Pump Manufacturer's name: <u>Goulds</u> Model No. <u>10BJ</u> HP <u>3/4</u> Volts <u>230</u>													
Depth of Pump Intake: <u>106</u> ft. Pumps Capacity rated at <u>10</u> gal./min.													
Type of pump: <u>1 Submersible</u> <u>2 Turbine</u> <u>3 Jet</u> <u>4 Centrifugal</u> <u>5 Reciprocating</u> <u>6 Other</u>													
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on <u>Sept.</u> month <u>6</u> day <u>1980</u> year													
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>179</u>													
This Water Well Record was completed on <u>Nov.</u> month <u>6</u> day <u>1980</u> year under the business name of <u>Joe's Well Service</u> <u>Cimarron, Kansas</u> by (signature) <u>Larry L. Crick</u>													
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:													
		FROM		TO		LITHOLOGIC LOG		FROM		TO		LITHOLOGIC LOG	
		0		15		Top soil & clay							
		15		30		Clay & fine sand							
		30		45		Fine sand							
		45		60		Fine sand & clay layers							
		60		75		Clay & medium to coarse sand (dry)							
		75		90		Coarse sand & clay layers							
		90		105		Fine to medium sand (with some coarse sand)							
105		120		Fine to medium sand (with some coarse sand) & clay layers									
120		150		Clay layers & fine to medium sand									
150		165		Fine to medium sand & clay									
ELEVATION:													
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)													

OFFICE USE ONLY

T

20

R

30

EW

SEC

30

NE

NE

NE

NE

NE

NE

NE

NE

NE

NE

NE

NE

NE