WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction			number	Township number	Range numbe	Range number	
1. Location of well:	Pinney	1/4 1/4	SW 1/4		9_	T 26	s R 32	<i>FM</i>	
. Distance and direction	on from nearest town or city:			ner of well	:	Raymond With	**:	P	
3/4 mi Rest. 3/4 mi. South of Plymell R.R. c					street:				
Street address of well location if in city: City, s					ode:	Copeland, Kansas 67837			
. Locate with "X" in s	ection below:	Sketch map:				6. Bore hole dia2	in. Completion d		
N						Well depth 370	_ft <u>3/22/</u>	6	
NW NE 50 ft. SE center of						7 Cable tool <u>X</u> Rotary Driven Dug			
						Hollow rod	JettedBored	Reverse rotary	
						8. Use: Domestic Public supply industry			
₩							Air conditioning Oil field water.		
SVE SE						9. Casing: Material			
	:]					Threaded Welder		12 in.	
S					-	RMP PVC _			
ı← 1 Mile			, ,			Dia. 16 in. to 370	ft. depth Wall Thickn	ss: inches or	
. Type and color of ma	terial			From	То	Dia in. to		17	
						10. Screen: Manufact	urer's name	 	
West Vell	3/8/76					Type mills	lot Dia. 16		
					~~	Slot/gauze_1/8_1	2** Length	57	
clay sand	· · · · · · · · · · · · · · · · · · ·			0	20	Set between 93 42	ft. and 37		
sand, som	e clay			20	40	Gravel pack? Yes:		4 4	
_					60	11. Static water level:		mo./day/yr.	
sand				40	60	72 ft. below l	and surface Date 🛂	12/76	
61ev ee	e cond			60	80	12. Pumping level belo			
clay, some sand					150 ft. after 15 hrs. pumping 200 4				
sand				80	100	Estimated maximum yie	nrs. pumping _	g.p.m.	
sand				100	120	13. Water sample subm		mo./day/yr.	
				1.55		Yes _ N	lo Date		
sand clay				120	140				
clay sand				140	160	Pitless adapter	12 Inches o	bove grade	
elay				160	180	15. Well grouted? Bentonite Concrete			
sand				180	180 200 Depth: From 0 ft. to 10 ft.			Concrete	
sand				200	220	16. Nearest source of p	possible contamination		
clay blus				220	240				
clay sand		·		240	260	Well disinfected upon	-	es No	
sand				260	280	17. Pump: Manufacturer's name _	X Not insta	illed	
- send		•		388	328	Model number	HP	_ Volts	
sand						Length of drop pipe	ft. capacity	g.p.m.	
sand, cla				320	340	Туре:			
sand, cla		y at 365	4. 000	340	36 6 0	Submersible Jet	:	urbine eciprocating	
clay, som	(Use a sec	drilled cond sheet if needed)	370	360	210	Centrifugal		other	
3. Elevation: 19.	. Remarks:					20. Water well contra	ctor's certification:		
						This well was drilled u		d this report	
opography:				_		is true to the best of m	y knowledge and belie	f. •≟ -	
pograpny: Hill				1	ligh	Plains Brill Business name	ing & Supp	Licers Vn	
Slope		*			402	Hith 3rd Go	rden City,	Ka 6784	
Upland						Signed Rup;	Harbren	Date 4-30	
Valley						Arthoriz	ed representative		