WATER WELL RECORD	Form WWC-5	Division of Wate	er Resources App. No	15801 D2	
1 LOCATION OF WATER WELL:	Fraction	Section Number	Township No.	Range Number	
County: FINNEY	1/4 NE 1/4 SW 1/4 NE		T 26 S	R 32 □E 🗹 W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					
15 M. SOUTH OF GARDEN ON HWY. 83 TO COUNTY LINE,			Longitude: (in decimal degrees)		
3 M. EAST, 3,950 FT. N. & 1,615 FT. W.		Elevation:	Elevation:		
2 WATER WELL OWNER: COLLINGWOOD TRUST			Datum: WGS 84, NAD 83, NAD 27		
RR#, Street Address, Box #: C/O WM. ENGLER, PO BOX 1184			Collection Method: GPS unit (Make/Model:)		
City, State, ZIP Code : HUTCHINSON, KS 67504		☐ Digital Map/Pl	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
Est. Accuracy:					
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 515 ft.					
SECTION BOX: Depth(s) Groundwater Encountered (1)					
N WELL'S STATIC WATER LEVEL242 ft. below land surface measured on mo/day/yr. 4-15-10					
Pump test data: Well water wasft. afterhours pumpinggpm EST. YIELDgpm. Well water wasft. afterhours pumpinggpm					
W ELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
					SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted					
Water well disinfected? Yes No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter16 in. to300 ft., Diameter ft., Diameter ft.					
Casing height above land surface					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Other (Specify) ☐ Brass ✓ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 300 ft. to 515 ft., From ft. to ft.					
SCREEN-I ERFORATED INTERVALS.	From ft. to	ft From	ft t	o ft	
GRAVEL PACK INTERVALS:	From 20 ft to 200) ft., From	260 ft. t	o 515 ft	
	From ft. to	ft., From	ft. t	o ft.	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From 0 ft. to 20 ft., From 200 ft. to 260 ft., From ft. to ft. to ft. What is the nearest source of possible contamination:					
	es Pit privy Livestoo		storage Othe	er (specify below)	
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ▼ Abandoned water well					
☐ Watertight sewer lines ☐ Seepage p Direction from well NORTHEAST		storage			
FROM TO LITHOLOG				GGING INTERVALS	
SEE ATTACHED LOG	6				
GEL ATTACHED EO		-		4.0 4.0	

7 CONTRACTORS OR LANDOWNER	CEDTIFICATION. This	oter well was 🗖	noted December	ustad on Daluared	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \(\mathbb{Z} \) constructed, \(\mathbb{D} \) reconstructed, or \(\mathbb{D} \) plugged under my jurisdiction and was completed on (mo/day/year). 4-15-10 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 4-20-10					
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Mora Keller					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy					
KSA 82a-1212		Check: 🔟 W	ше Сору, 🔲 Вій	e Copy, 🔲 Pink Copy	

MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Domestic and Repairing

INCORPORATED

Phone 276-8269 P.O. Box A **GARDEN CITY, KANSAS 67846**

JLM Farms Finney County 1/26/05

Location: NEt 33-26-32 - South on Hwy. 83 to Lear Road, 3 miles east, mile south & mile west - 300 ft. west of well

Static Water Level - 210 ft.

Test #2

0' to 1' - Top soil 1' to 18' - Brown clay 18' to 42' - Brown sandy clay 42' to 120' - Fine to medium sand & gravel - some coarse 120' to 154' - Brown clay 154' to 163' - Fine to medium sand & gravel 163' to 174' - Brown clay 174' to 218' - Fine to medium sand & gravel - 10% clay 218' to 238' - Brown sandy clay 238' to 248' - Brown clay - small gravel streaks 248' to 331' - Fine to medium sand & gravel 331' to 349' - Brown sandy clay 349' to 361' - Fine to medium sand & gravel 361' to 445' - Brown sandy clay 445' to 448' - Fine to medium sand & fine gravel 448' to 460' - Brown clay 460' to 475' - Fine to medium sand & gravel 475' to 479' - Fine to medium sand & gravel - clay strip 479' to 488' - Fine to medium sand & gravel 488' to 506' - Brown clay 506' to 511' - Brown clay with 30% brown rock 511' to 521' - Brown yellow clay 521' to 530' - Red bed