WATER WELL RECORD	Form WWC-5	Division of Wate	er Resources App. N	875 & 16076
1 LOCATION OF WATER WELL:	Fraction	Section Number	Township No.	Range Number
County: FINNEY			T 26 S	R 32 □E ☑W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here				
GARDEN CITY 15 MILES SOUTH TO COUNTY LINE,2 MILES		Longitude: (in decimal degrees)		
EAST 3805'N. 4430'W.		Elevation:		
2 WATER WELL OWNER: MARION LOBMEYER		Datum: WGS 84, NAD 83, NAD 27 Collection Method:		
RR#, Street Address, Box #: 14420 S. RD. 14		GPS unit (Make/Model:)		
City, State, ZIP Code : GARDE	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL				
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL .466 ft. SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft				
SECTION BOX: Depth(s) Groundwater Encountered (1)				
Pump test data: Well water wasft. after hours pumping gpm				
EST. YIELDgpm. Well water was				
W Bore Hole Diameter 30				
-SW SE - Domestic Feedlot Oil field water supply Dewatering Other (Specify below)				
☐ ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well				
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted				
S If yes, mo/day/yr sample was submitted				
5 TYPE OF CASING USED: Steel PVC Other				
CASING JOINTS: Glued Clamped W Welded Threaded				
Casing diameter .16 in. to .286 ft., Diameter in. to ft., Diameter ft.				
Casing height above land surface. 12				
TYPE OF SCREEN OR PERFORATION MATERIAL: ✓ Steel Stainless Steel PVC Other (Specify)				
Brass Galvanized Steel None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)				
SCREEN-PERFORATED INTERVALS: From				
From				
From				
6 GROUT MATERIAL: ☐ Neat cement ☑ Cement grout ☐ Bentonite ☐ Other				
Grout Intervals: From .0				
What is the nearest source of possible conta	es Pit privy Livestoc	pens Insecticid	e storage	ner (specify below)
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well				
☐ Watertight sewer lines ☐ Seepage p Direction from well				
FROM TO LITHOLOG				IGGING INTERVALS
			- SPV*	
SEE ATTACHED LOG				
SEE ATTACHED COG				
		100		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged				
under my jurisdiction and was completed on (mo/day/year) .61510 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 6-16-10 under the business name of .MINTER WILSON DRILLING CO. INC by (signature)				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies				
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at				
http://www.kdheks.gov/waterwell/index.html.				
KSA 82a-1212		Check: V W	hite Copy, 🔲 Bl	ue Copy, 🔲 Pink Copy

The Professionals MINTER-WILSON DRILLING CO

Irrigation and Domestic **Water Systems** Complete Installation and Repairing

INCORPORATED

Phone 620-276-8269 P.O. Box A • **GARDEN CITY, KANSAS 67846**

NAME

MARION LOBMEYER

COUNTY

FINNEY

DATE

4-21-10

LOCATION:

NW 1/4 32-26-32 - SOUTH OF GARDEN CITY ON HWY. 83 TO

LEAR ROAD - 1 MILE EAST & 1/2 MILE SOUTH

STATIC WATER LEVEL - APPROX. 250 FT.

TEST #1

0' TO 1' - TOP SOIL

1' TO 27' - BROWN SANDY CLAY

27' TO 89' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

89' TO 115' - BROWN SANDY CLAY

115' TO 128' - BROWN SANDY CLAY

WITH STRIPS OF SAND, GRAVEL & HARD WHITE ROCK

128' TO 138' - FINE TO MEDIUM SAND & GRAVEL

138' TO 172' - BROWN CLAY

172' TO 187' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN CLAY

187' TO 216' - BROWN & GRAY CLAY

216' TO 290' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF CLAY 10%

290' TO 304' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY 25%

304' TO 356' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK

356' TO 365' - BROWN SANDY CLAY WITH STRIPS OF SAND 15%

365' TO 382' - FINE TO MEDIUM SAND

WITH STRIPS OF BROWN SANDY CLAY 20%

382' TO 418' - BROWN CLAY WITH STRIPS OF SAND

418' TO 440' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN & YELLOW CLAY 25%

440' TO 454' - FINE TO MEDIUM SAND & GRAVEL WITH SOME BROWN ROCK

454' TO 459' - HARD BROWN & YELLOW CLAY

459' TO 470' - GRAY SHALE WITH BROWN & YELLOW CLAY-300 PULL DOWN