WATER WELL RECORD	Form WWC-5	Division of Water	Resources App. No	9796			
1 LOCATION OF WATER WELL:	Fraction	Section Number		Range Number			
County: FINNEY	14 NE 14 NW 14 NE 14	26	T 26 S	R 32 □E 🗹 W			
Street/Rural Address of Well Location;	if unknown, distance & direction	Global Positioning	System (GPS) in	formation:			
from nearest town or intersection: If at	owner's address, check here .			(in decimal degrees)			
GARDEN CITY-14 M S ON HWY 8	3 TO LEAR ROAD, 5 M E.			(in decimal degrees)			
5,235 FT. NORTH & 1,480 FT. WE		Elevation:					
Maria Maria		Datum: WGS 84, NAD 83, NAD 27					
TABIAI	N DUESING ESTATE C/O S DUESING, PO BOX 97	Collection Method:	/Model:)			
City City City				c Map, Land Survey			
SPEAR	VILLE, KS 67876	Est. Accuracy:					
3 LOCATE WELL	=00						
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL 520	ft.					
SECTION BOX: Depth(s) Ground	dwater Encountered (1)	ft. (2)	ft. (3) ft.			
	IC WATER LEVELft.	below land surface m	easured on mo/d	ay/yr12-17-10			
NA NE P	-NW - -NE - EST. YIELD						
	TO BE USED AS: Public wate	r supply	unermai II	njection well			
swse ☐ Domestic ☐ Irrigation							
	bacteriological sample submitted to	Department?	Zes 1 No				
	day/yr sample was submitted		ics w No				
	nfected? Yes No	•••••					
Water wen also							
5 TYPE OF CASING USED: Stee							
CASING JOINTS: Glued Clar	nped Welded Threaded	0 D:					
Casing diameter .16 in. to .290. Casing height above land surface12	II., Diameter in. t	0 II., Di	ameter	. in. to It.			
TYPE OF SCREEN OR PERFORATION	MATERIAL	lbs./it., wall thich	kness or gauge No	0			
✓ Steel Stainless Steel		Other (Specify)					
	☐ None used (open hole)	Other (Specify)		•••••			
SCREEN OR PERFORATION OPENING							
☐ Continuous slot	☐ Gauze wrapped ☐ Torch cut		None (open hole				
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS:							
	From ft. to	ft., From	ft. 1	to ft.			
GRAVEL PACK INTERVALS:	From 20 ft to 210						
COPOUT MATERIAL.	From ft. to						
6 GROUT MATERIAL: ☐ Neat ceme Grout Intervals: From 0	ent V Cement grout Benton 520 ft., From f	otte U Otner		Δ 4- Δ			
What is the nearest source of possible contra		ι. ιο 1ι.,	rrom	. п. юп.			
	nes Pit privy Livestock p	ens 🔲 Insecticide	storage D Oth	er (specify below)			
Sewer lines Cesspool	Sewage lagoon Fuel storage		water well	or (specify octow)			
☐ Watertight sewer lines ☐ Seepage	oit Feedyard Fertilizer sto						
Direction from well	Distance f	rom well					
FROM TO LITHOLOG	FROM FROM	TO LITHO. LO	G (cont.) or PLU	GGING INTERVALS			
SEE ATTACHED LOG							
				<u> </u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) .12-17-10 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 12-20-10							
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Mora Keller.							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME

PHIL DUESING

COUNTY

FINNEY

DATE

11-18-10

LOCATION:

NE 1/4 26-26-32 - SOUTH ON HWY, 83 TO LEAR ROAD.

5 MILES EAST, 1 MILE NORTH &

1/4 MILE WEST

- NORTH EDGE OF CIRCLE

STATIC WATER LEVEL - 240 FT.

TEST#3

n' TO	1'-	TOP	SOIL

1' TO 48' - BROWN SANDY CLAY

48' TO 78' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

78' TO 86' - BROWN SANDY CLAY

86' TO 104' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

104' TO 120' - BROWN CLAY

120' TO 147' - GREEN & WHITE CLAY WITH STRIPS IF HARD WHITE ROCK

147' TO 152' - FINE TO MEDIUM SAND

152' TO 168' - BLUE CLAY WITH STRIPS OF HARD WHITE ROCK

168' TO 171' - FINE TO MEDIUM SAND

171' TO 229' - BLUE CLAY WITH STRIPS OF SAND

229' TO 234' - FINE TO MEDIUM SAND & GRAVEL

234' TO 240' - BROWN CLAY

240' TO 247' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

247' TO 263' - BROWN CLAY WITH STRIPS OF WHITE ROCK

263' TO 272' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL - 30%

272' TO 304' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

304' TO 308' - BROWN SANDY CLAY

308' TO 336' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY - 30%

336' TO 355' - BROWN SANDY CLAY

355' TO 374' - FINE TO MEDIUM SAND & GRAVEL

374' TO 460' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK & SAND - 10%

460' TO 463' - FINE TO MEDIUM SAND

463' TO 466' - BROWN CLAY

466' TO 470' - FINE TO MEDIUM SAND & GRAVEL

470' TO 493' - BROWN CLAY

493' TO 498' - FINE TO MEDIUM SAND & GRAVEL WITH SOME BROWN ROCK

498' TO 510' - HARD BROWN & YELLOW CLAY WITH 20% BROWN ROCK

510' TO 519' - BROWN & YELLOW CLAY WITH 40% BROWN ROCK

519' TO 530' - SHALE - 250 PULL DOWN