WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.		1,395	
1 LOCATION OF WATER WELL:		Fraction		Section Number Township No.		Range Number	
County: FINNEY		1/4 NE 1/4 SE		18	T 26 S		□E ØW
Street/Rural Address of Well Location; if unknown, distance & dir from nearest town or intersection: If at owner's address, check her				Global Positioning System (GPS) information: Latitude:			
,				Longitude: (in decimal degrees)			
GARDEN CITY-12 M S. ON HWY 83 TO TV ROAD, 1 M E, 3,622 FT. NORTH & 45 FT. WEST				Elevation:			
· · ·				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: RICHARD & JEAN STRANDMARK RR#, Street Address, Box #: 1408 MELS DRIVE				Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code		N CITY, KS 67846		Digital Map/Photo, Topographic Map, Land Survey			
	GARDE	.N CITT, NS 07040		Est. Accuracy: -	3 m, 🔲 3-5 m, 🔲	5-15 m, 🔲	>15 m
3 LOCATE WELL	4 DEDTH OF	COMDITED WELL	r 495	A			
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1) ft (2) ft (3) ft							
SECTION BOX: Depth(s) Groundwater Encountered (1)							
Pump test data: Well water wasft. after hours pumping gpm							
EST. YIELDgpm. Well water wasft. after							
W Bore Hole Diameter30 in. to495 ft., and in. to							
	WELL WATER ☐ Domestic	TO BE USED AS: L] Public wate	er supply	otnermal III		
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below) ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No							
S If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected? ☐ Yes ☑ No							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .16 in to .280 ft., Diameter in to							
Casing height above land surface12							
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)							
Brass Galvanized Steel None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous slot							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From 280 ft., From ft., From ft.							
From							
GRAVEL PACK INTERVALS: From 30 ft. to 200 ft., From 260 ft. to 495 ft. From ft. to							
6 GROUT MATERIAL	□ Neat ceme	ent Cement grout	☐ Benton	ite		J	11.
Grout Intervals: From	.0	30 ft., From	200	ft. to 260 ft.,	From	ft. to	ft.
What is the nearest source				•			
						er (specify be	elow)
Sewer lines Watertight sewer lin	Cesspool		☐ Fuel storage ☐ Fertilizer st		A I / A		
Direction from well				from well			
FROM TO	LITHOLOG	IC LOG	FROM	TO LITHO LO	OG (cont.) <u>or</u> PLU	GGING IN	TERVALS
OEE AT	TACHEDIOC						
J SEE AI	TACHED LOG		 				
			<u>L</u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) .1-7-11							
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature)							
INSTRUCTIONS: Use typewr	iter or ball point pen	. PLEASE PRESS FIRMLY	and <u>PRINT</u> cle	arly. Please fill in blanks	and check the correct	answers. Ser	nd three copies
(white, blue, pink) to Kansas D Telephone 785-296-5522. Send							
http://www.kdheks.gov/waterwel		DK WELL OWNER and I	van one tor y	our records. Menute let	or \$5.00 for each co	WC	+ 151t us at
KSA 82a-1212				Check: 🗗 Wl	nite Copy, 🔲 Blu	е Сору,	Pink Copy

The Professionals MINTER-WILSON DRILLING CO. Urrigation and Domestic Water Systems Complete Installation

Irrigation and Repairing

INCORPORATED

Phone 620-276-8269 P.O. Box A • **GARDEN CITY, KANSAS 67846**

NAME

DEAN KLEYSTEUBER

COUNTY DATE

FINNEY 10-12-10

LOCATION:

NE 1/4 18-26-32 - HWY. 83 & PLYMELL ROAD - 1 MILE EAST,

1-1/8TH MILE SOUTH ON WEST SIDE - 550 FT. SOUTH OF EXISTING WELL

STATIC WATER LEVEL - 250 FT.

TEST#2

0' TO 12' - BROWN SANDY CLAY

12' TO 26' - FINE TO MEDIUM SAND

26' TO 38' - BROWN SANDY CLAY WITH STRIPS OF SAND & GRAVEL

38' TO 75' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

75' TO 97' - BROWN CLAY

97' TO 108' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY

108' TO 123' - BROWN SANDY CLAY

123' TO 169' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE WITH STRIPS OF BROWN SANDY CLAY

169' TO 175' - BROWN CLAY

175' TO 203' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY

203' TO 248' - BROWN SANDY CLAY

248' TO 255' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

255' TO 285' - FINE TO MEDIUM SAND & GRAVEL

285' TO 307' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 20%

307' TO 310' - BROWN SANDY CLAY

310' TO 317' - FINE TO MEDIUM SAND & GRAVEL

317' TO 332' - BROWN SANDY CLAY

332' TO 341' - FINE TO MEDIUM SAND & GRAVEL

WITH STRIPS OF BROWN SANDY CLAY - 30%

341' TO 349' - BROWN SANDY CLAY

349' TO 352' - FINE TO MEDIUM SAND & GRAVEL

352' TO 382' - BROWN SANDY CLAY WITH STRIPS OF HARD WHITE ROCK

382' TO 385' - FINE TO MEDIUM SAND

385' TO 389' - BROWN SANDY CLAY WITH STRIPS OF HARD WHITE ROCK

389' TO 397' - BROWN SANDY CLAY & FINE TO MEDIUM SAND MIXED-50/50

397' TO 430' - BROWN SANDY CLAY WITH STRIPS OF HARD WHITE ROCK

430' TO 444' - BROWN SANDY CLAY & WHITE ROCK

WITH STRIPS OF FINE TO MEDIUM SAND - 20%

444' TO 452' - FINE TO MEDIUM SAND & GRAVEL - SOME BROWN ROCK

452' TO 473' - BROWN SANDY CLAY

WITH STRIPS OF SAND & BROWN ROCK - 10%

473' TO 492' - HARD BROWN & YELLOW CLAY WITH 10% BROWN ROCK - 250 PULL DOWN

492' TO 495' - SOFT BROWN & YELLOW CLAY WITH 30% BROWN ROCK

495' TO 500' - SHALE