WATER WELL RECOR	D	Form WV	NC-5	Division of Wate	r Resources App. No	15801 D3
1 LOCATION OF WATER WELL:		Fraction		Section Number	Township No.	Range Number
County: FINNEY		1/4 SW 1/4 NE	1/4 SW 1/4	22 Clobal Pasitioning	T 26 S	R 32 □E ✔W
from nearest town or interse	owner's address, check	here \square .	Latitude:			
GARDEN CITY-10 M. S. ON HWY, 83 TO PLYMELL RD, 4 M. E.			Longitude: (in decimal degrees)			
3 M. S., 1350 FT. N. & 3840 FT. W						
2 WATER WELL OWNER: EDNA COLLINGWOOD TRUST			JST	Datum: WGS 84, NAD 83, NAD 27 Collection Method:		
RR#, Street Address, Box #	X 1184		GPS unit (Make/Model:)			
City, State, ZIP Code	INSON, KS. 67504		Digital Map/Photo, Topographic Map, Land Survey Est Accuracy: $\Box < 3 \text{ m}$ $\Box = 3.5 \text{ m}$ $\Box = 5.15 \text{ m}$			
3 LOCATE WELL		Lat. Accuracy.	5 m, 🗀 5-5 m, 🖵	5-15 m, > 15 m		
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL						
SECTION BOX: Depth(s) Groundwater Encountered (1)						
Pump test data: Well water was						ping
W NE E EST. YIELD						
$[sw^{A_{-}}]_{sw^{A_{-}}}$ $[-sw^{A_{-}}]_{sw^{A_{-}}}$						
Was a chemical/bacteriological sample submitted to Department? Yes No						
S If yes, mo/day/yr sample was submitted						
Water well disinfected? Ves V No						
5 TYPE OF CASING USED: Steel PVC Other						
Casing diameter 16 in to 275 ft Diameter 16 in to 395 ft Diameter in to ft						
Casing height above land surface. 12 in, Weight 42.05 lbs./ft., Wall thickness or gauge No						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel PVC Other (Specify)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot V Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
From						
GRAVEL PACK INTERVALS: From 20						to
From						
6 GROUT MATERIAL: [] Neat cement ♥] Cement grout [] Bentonite [] Other						
What is the nearest source of possible contamination:						
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage ♥ Abandoned water well						
Direction from well SOU	THWEST		Distance	from well 30 FT.	& 120 FT, W	
FROM TO	LITHOLOG	GIC LOG	FROM	TO LITHO. L	OG (cont.) <u>or</u> PLU	JGGING INTERVALS
SECANA						
		•				
		·····			·····	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🖉 constructed, 🗌 reconstructed, or 🗌 plugged						
under my jurisdiction and was completed on (mo/day/year). 2-21-11 and this record is true to the best of my knowledge and belief.						
under the husiness name of MINTER-WILSON DRILLING CO., INC. by (signature) The Kuller						
INSTRUCTIONS: Use typewriter	or ball point pe	n. <u>PLEASE PRESS FIRML</u>	and <u>PRINT</u> cle	arly. Please fill in blank	s and check the correct	ct answers. Send three copies
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
http://www.kdheks.gov/waterwell/index.html.						

The Professionals MINTER-WILSON DRILLING CO. Water Systems Complete Installation

and Repairing

Irrigation

INCORPORATED

Phone 620-276-8269 P.O. Box A • GARDEN CITY, KANSAS 67846

NAME COLLINGWOOD TRUST TENANT ED BANNING FINNEY COUNTY DATE 11-15-10

SW 1/4 22-26-32 - SOUTH ON HWY. 83 TO PLYMELL ROAD -LOCATION: 3 MILES EAST, 2-3/4 MILES SOUTH & 1/4 OF A MILE EAST

STATIC WATER LEVEL - 245 FT.

TEST #1

- 0' TO 3' - TOP SOIL
- 3' TO 53' BROWN SANDY CLAY
- 53' TO 102' FINE TO MEDIUM SAND & GRAVEL SOME COARSE
- 102' TO 115' BROWN SANDY CLAY
- 115' TO 134' FINE TO MEDIUM SAND & GRAVEL WITH LAYERS OF BROWN SANDY CLAY
- 134' TO 137' CEMENTED SAND 250 PULL DOWN
- 137' TO 147' BROWN CLAY

WITH STRIPS OF WHITE CLAY & WHITE ROCK

147' TO 188' - BROWN SANDY CLAY

WITH STRIPS OF WHITE ROCK

- 188' TO 212' FINE TO MEDIUM SAND & GRAVEL SOME COARSE
- 212' TO 225' BROWN CLAY
- 225' TO 244' BLUE CLAY SLUFFED ALL THE WAY TO BOTTOM
- 244' TO 256' FINE TO MEDIUM SAND & GRAVEL
- 256' TO 259' BROWN SANDY CLAY

259' TO 290' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

290' TO 302' - FINE TO MEDIUM SAND & GRAVEL - TIGHT

302' TO 311' - FINE TO MEDIUM SAND & GRAVEL

- 311' TO 347' BROWN SANDY CLAY
- 347' TO 349' FINE TO MEDIUM SAND & GRAVEL

349' TO 429' - BROWN SANDY CLAY WITH STRIPS OF HARD WHITE ROCK

429' TO 438' - BROWN SANDY CLAY

WITH STRIPS OF FINE TO MEDIUM SAND - 30%

- 438' TO 455' FINE TO MEDIUM SAND SOME SMALL GRAVEL WITH STRIPS OF BROWN SCLAY - 20%
- 455' TO 462' FINE TO MEDIUM SAND WITH SOME BROWN ROCK 462' TO 478' - BROWN CLAY
- 478' TO 481' FINE TO MEDIUM SAND & BROWN ROCK LOOSE

481' TO 505' - BROWN & YELLOW CLAY WITH 20% BROWN ROCK

505' TO 519' - BROWN & YELLOW CLAY WITH 40% BROWN ROCK

519' TO 530' - SHALE - 250 PULL DOWN