

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

33,902

1 LOCATION OF WATER WELL: County: FINNEY		Fraction ¼ SW ¼ SW ¼ SE ¼		Section Number 36		Township No. T 26 S		Range Number R 32 <input type="checkbox"/> E <input checked="" type="checkbox"/> W																																																																									
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here <input type="checkbox"/> 15 M S OF GARDEN CITY TO HASKELL CO. LINE, 6 M E, 1,405 FT. NORTH & 2,630 FT. WEST				Global Positioning System (GPS) information: Latitude: 37.74034 (in decimal degrees) Longitude: 100.77021 (in decimal degrees) Elevation: Datum: <input type="checkbox"/> WGS 84, <input type="checkbox"/> NAD 83, <input checked="" type="checkbox"/> NAD 27 Collection Method: <input checked="" type="checkbox"/> GPS unit (Make/Model: GARMIN 62ST) <input type="checkbox"/> Digital Map/Photo, <input type="checkbox"/> Topographic Map, <input type="checkbox"/> Land Survey Est. Accuracy: <input type="checkbox"/> <3 m, <input type="checkbox"/> 3-5 m, <input type="checkbox"/> 5-15 m, <input type="checkbox"/> >15 m																																																																													
2 WATER WELL OWNER: BILL HEIMAN RR#, Street Address, Box #: 2121 BUFFALO HEIGHTS DR City, State, ZIP Code : GARDEN CITY, KANSAS 67846																																																																																	
3 LOCATE WELL WITH AN "X" IN SECTION BOX: N <table border="1" style="width:100%; text-align: center; border-collapse: collapse;"> <tr> <td style="width:25%;">NW</td> <td style="width:25%;">NE</td> <td style="width:25%;">E</td> </tr> <tr> <td>SW</td> <td>SE</td> <td></td> </tr> </table> S -----1 mile-----				NW	NE	E	SW	SE		4 DEPTH OF COMPLETED WELL 495 ft. Depth(s) Groundwater Encountered (1)..... ft. (2)..... ft. (3)..... ft. WELL'S STATIC WATER LEVEL 225 ft. below land surface measured on mo/day/yr. 6-8-12 Pump test data: Well water was ft. after hours pumping gpm EST. YIELD..... gpm. Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 495 ft., and in. to ft. WELL WATER TO BE USED AS: <input type="checkbox"/> Public water supply <input type="checkbox"/> Geothermal <input type="checkbox"/> Injection well <input type="checkbox"/> Domestic <input type="checkbox"/> Feedlot <input type="checkbox"/> Oil field water supply <input type="checkbox"/> Dewatering <input type="checkbox"/> Other (Specify below) <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Industrial <input type="checkbox"/> Domestic-lawn & garden <input type="checkbox"/> Monitoring well Was a chemical/bacteriological sample submitted to Department? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If yes, mo/day/yr sample was submitted..... Water well disinfected? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																																																							
NW	NE	E																																																																															
SW	SE																																																																																
5 TYPE OF CASING USED: <input checked="" type="checkbox"/> Steel <input type="checkbox"/> PVC <input type="checkbox"/> Other CASING JOINTS: <input type="checkbox"/> Glued <input type="checkbox"/> Clamped <input checked="" type="checkbox"/> Welded <input type="checkbox"/> Threaded Casing diameter 16 in. to 280 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 12 in., Weight 42.05 lbs./ft., Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: <input checked="" type="checkbox"/> Steel <input type="checkbox"/> Stainless Steel <input type="checkbox"/> PVC <input type="checkbox"/> Other (Specify) <input type="checkbox"/> Brass <input type="checkbox"/> Galvanized Steel <input type="checkbox"/> None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: <input type="checkbox"/> Continuous slot <input checked="" type="checkbox"/> Mill slot <input type="checkbox"/> Gauze wrapped <input type="checkbox"/> Torch cut <input type="checkbox"/> Drilled holes <input type="checkbox"/> None (open hole) <input type="checkbox"/> Louvered shutter <input type="checkbox"/> Key punched <input checked="" type="checkbox"/> Wire wrapped <input type="checkbox"/> Saw cut <input type="checkbox"/> Other (specify) SCREEN-PERFORATED INTERVALS: From 280 ft. to 400 ft., From 430 ft. to 495 ft. GRAVEL PACK INTERVALS: From 20 ft. to 205 ft., From 265 ft. to 495 ft. From ft. to ft., From ft. to ft.																																																																																	
6 GROUT MATERIAL: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Cement grout <input type="checkbox"/> Bentonite <input type="checkbox"/> Other Grout Intervals: From 0 ft. to 20 ft., From 205 ft. to 265 ft., From ft. to ft. What is the nearest source of possible contamination: <input type="checkbox"/> Septic tank <input type="checkbox"/> Lateral lines <input type="checkbox"/> Pit privy <input type="checkbox"/> Livestock pens <input type="checkbox"/> Insecticide storage <input type="checkbox"/> Other (specify below) <input type="checkbox"/> Sewer lines <input type="checkbox"/> Cesspool <input type="checkbox"/> Sewage lagoon <input type="checkbox"/> Fuel storage <input type="checkbox"/> Abandoned water well <input type="checkbox"/> Watertight sewer lines <input type="checkbox"/> Seepage pit <input type="checkbox"/> Feedyard <input type="checkbox"/> Fertilizer storage <input type="checkbox"/> Oil well/gas well N/A Direction from well Distance from well																																																																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>LITHO. LOG (cont.) or PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>280</td> <td>16" PLAIN CASING</td> <td></td> <td></td> <td></td> </tr> <tr> <td>280</td> <td>300</td> <td>16" JOHNSON AGRI SCREEN</td> <td></td> <td></td> <td></td> </tr> <tr> <td>300</td> <td>320</td> <td>16" MILL SLOT PERF.</td> <td></td> <td></td> <td>SEE ATTACHED LOG</td> </tr> <tr> <td>320</td> <td>400</td> <td>16" JOHNSON AGRI SCREEN</td> <td></td> <td></td> <td></td> </tr> <tr> <td>400</td> <td>430</td> <td>16" PLAIN CASING</td> <td></td> <td></td> <td></td> </tr> <tr> <td>430</td> <td>490</td> <td>16" JOHNSON AGRI SCREEN</td> <td></td> <td></td> <td></td> </tr> <tr> <td>490</td> <td>495</td> <td>16" MILL SLOT PERF.</td> <td></td> <td></td> <td></td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS	0	280	16" PLAIN CASING				280	300	16" JOHNSON AGRI SCREEN				300	320	16" MILL SLOT PERF.			SEE ATTACHED LOG	320	400	16" JOHNSON AGRI SCREEN				400	430	16" PLAIN CASING				430	490	16" JOHNSON AGRI SCREEN				490	495	16" MILL SLOT PERF.																											
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS																																																																												
0	280	16" PLAIN CASING																																																																															
280	300	16" JOHNSON AGRI SCREEN																																																																															
300	320	16" MILL SLOT PERF.			SEE ATTACHED LOG																																																																												
320	400	16" JOHNSON AGRI SCREEN																																																																															
400	430	16" PLAIN CASING																																																																															
430	490	16" JOHNSON AGRI SCREEN																																																																															
490	495	16" MILL SLOT PERF.																																																																															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, <input type="checkbox"/> reconstructed, or <input type="checkbox"/> plugged under my jurisdiction and was completed on (mo/day/year) 6-8-12 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 6-12-12 under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) <i>Nora Keller</i> INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html .																																																																																	

*The
Professionals*

MINTER-WILSON DRILLING CO.

INCORPORATED

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

Phone 620-276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

NAME BILL HEIMAN
COUNTY FINNEY
DATE 3-17-12

LOCATION: SE 1/4 36-26-32 - SOUTH OF GARDEN CITY TO LEAR ROAD -
5-1/2 MILES EAST, 3/4 OF A MILE SOUTH
ON THE EAST SIDE

STATIC WATER LEVEL -

TEST # 3

0' TO 35' - BROWN SANDY CLAY
35' TO 132' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE
132' TO 145' - BROWN CLAY
145' TO 168' - BLUE CLAY
168' TO 173' - BLUE SAND
173' TO 180' - BLUE CLAY WITH STRIPS OF SAND
180' TO 240' - BLUE SAND WITH STRIPS OF BLUE CLAY & WHITE ROCK
240' TO 265' - BROWN SANDY CLAY
265' TO 276' - FINE TO MEDIUM SAND & GRAVEL
276' TO 279' - BROWN SANDY CLAY
279' TO 296' - FINE TO MEDIUM SAND & GRAVEL
296' TO 300' - FINE TO MEDIUM SAND & GRAVEL
WITH STRIPS OF WHITE ROCK - 40% - DRILLED TIGHT
300' TO 324' - BROWN SANDY CLAY
324' TO 330' - FINE TO MEDIUM SAND & GRAVEL
330' TO 335' - BROWN SANDY CLAY
335' TO 340' - FINE TO MEDIUM SAND & GRAVEL
340' TO 354' - BROWN CLAY
354' TO 365' - FINE TO MEDIUM SAND
WITH STRIPS OF BROWN SANDY CLAY - 20%
365' TO 377' - BROWN SANDY CLAY
377' TO 387' - FINE TO MEDIUM SAND
387' TO 410' - BROWN SANDY CLAY WITH STRIPS OF WHITE ROCK
410' TO 436' - BROWN CLAY
436' TO 445' - FINE TO MEDIUM SAND
WITH STRIPS OF BROWN SANDY CLAY - 25%
445' TO 469' - FINE TO MEDIUM SAND WITH 15% BROWN ROCK
469' TO 485' - BROWN & YELLOW CLAY WITH 30% BROWN ROCK
485' TO 495' - HARD BROWN & YELLOW CLAY WITH 10% BROWN ROCK
495' TO 515' - SHALE