


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County FINNEY	Fraction NW 1/4 SE 1/4 NW 1/4	Section number 30	Township number T 26 S	Range number R 33 E/W
2. Distance and direction from nearest town or city: Plymell 5 3/4 west 1/4 south			3. Owner of well: Fern Catchelder Batchelder R.R. or street: 1706 B St. City, state, zip code: Garden City, Ks. 67846		
4. Locate with "X" in section below: 			Sketch map:		
5. Type and color of material			From	To	6. Bore hole dia. 26 in. Completion date 5-31-76 Well depth 340 ft.
					7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary
					8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other
					9. Casing: Material steel Height: above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 34 1/2 ft. depth Wall thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 219 mhc
					10. Screen: Manufacturer's name Johnson Division Type Galv. Dia. 16" Slot/gauze 100 Length 20' Set between 300 ft. and 320 ft. Perf. 160-300 ft. and 320-340 ft. Gravel pack? yes Size range of material 1/8" to 1/4" down
					11. Static water level: <input type="checkbox"/> mo./day/yr. 122 ft. below land surface Date 5-26-76
					12. Pumping level below land surfaces: 1350 126 ft. after 5 hrs. pumping 1350 g.p.m. 126 ft. after 1 hrs. pumping 1350 g.p.m. Estimated maximum yield 1350 g.p.m.
					13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date 5-26-76
					14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade
					15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft. N/A
					16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input checked="" type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
					17. Pump: Not installed Manufacturer's name Gould National Pump Model number 12HC HP 125 Volts 1000 Length of drop pipe 220 ft. capacity 1000 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
(Use a second sheet if needed)					
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling 208 Business Box A Garden City, Ks. Address Box A Garden City, Ks. Signed M. Wilson Date 5-12-76 Authorized representative		
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input type="checkbox"/> Upland <input type="checkbox"/> Valley					

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

**FERN BATCHELDER
FINNEY COUNTY
2-18-76**

**LOCATION: NW 30-26-33
Center Of Quarter, At Pivot**

STATIC WATER LEVEL: 126

CIRCLE #7

0	3	Top Soil
3	62	Brown Sandy Clay
62	95	Fine To Med. Sand & Gravel (Loose)
95	112	Med. To Coarse Gravel
112	120	Fine To Med. Sand & Gravel, Streaks Of Clay (10%)
120	128	Fine To Med. Sand & Gravel, Streaks Of Clay (20%)
128	182	Fine To Med. Sand & Gravel, Streaks Of Clay (10%)
182	190	Fine To Med. Sand & Gravel, Streaks Of Clay (20%) Tight
190	215	Fine To Med. Sand & Gravel, Streaks Of Clay (10%)
215	230	Fine To Med Sand & Gravel, Streaks Of Blue Clay (20%)
230	251	Blue Clay
251	260	Fine To Med Sand & Gravel, Streaks Of Clay (10%)
260	340	Fine To Med. Sand & Gravel (Loose)
340	350	Fine To Med. Sand & Gravel, Streaks Of Clay (25%) Tight
350	382	Brown Sandy Clay, Streaks Of Gray Clay (10%) Tight
382	400	Brown Clay, White Clay, Streaks Of Yellow Clay (Hard)

Used Pulldown TD340 20' Screen