WATER WELL RECORD	Form WWC-5	Division of Wate	r Resources App. N	0.	
1 LOCATION OF WATER WELL:	Fraction	1	Township No.		
County: FINNEY	1/4 NW 1/4 NE 1/4LOT2 1/4	6	T 26 S	R 33 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					
	Latitude: (in decimal degrees)				
GARDEN CITY, 9 M S ON HWY. 83 TO PARALLEL RD, 5 M W,		Longitude: (in decimal degrees)			
1-1/3RDS M S, 6939 FT N & 2525 FT W		Elevation:			
2 WATER WELL OWNER: WHEATLAND ELECTRIC COOP INC		Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: PO BOX 230		GPS unit (Make/Model:)			
		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, State, ZIP Code : SCOTT CITY, KS 67871		Est. Accuracy:			
3 LOCATE WELL					
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 475 ft.					
SECTION BOX: Depth(s) Ground	Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.				
N WELL'S STAT	IC WATER LEVEL227ft.	t. below land surface measured on mo/day/yr3-4-11			
Y Pump	Pump test data: Well water wasft. after hours pumping gpm				
DOT VIELD	EST. YIELD				
WNWNE Bore Hole Diam	Bore Hole Diameter 30 in. to 475 ft., and in. to ft.				
	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well				
Domestic Decodlet Oil field water symply Developing Other (Specify below)					
SW SE Domestic Feedfor Domestic-lawn & garden Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes V No					
s If yes, mo/day/yr sample was submitted					
Water well disinfected? ☐ Yes ✓ No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped M Welded Threaded					
Casing diameter 16 in to 285 ft., Diameter in to ft., Diameter in to ft.					
Casing height above land surface					
TYPE OF SCREEN OR PERFORATION					
✓ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From 285 ft. to 475 ft., From ft. to ft.					
From					
GRAVEL PACK INTERVALS: From 20 ft. to 205 ft., From 265 ft. to 475 ft.					
From					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From 0 ft. to 20 ft., From 205 ft. to 265 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well					
Sewer lines Cesspoor Sewage lagoon Fuel storage Abandoned water wen Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well N/A					
Direction from well Distance from well					
FROM TO LITHOLOG				JGGING INTERVALS	
TROW TO ENTIONE	ile Loc	TO DITTO. D.	oo (cont.) of T.C.	DOGINO INTERVALS	
	+ +				
OFF ATTACHED LOG					
SEE ATTACHED LOG					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) 3-4-11 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/year) 3-7-11					
under the business name of MINTER-WILSON DRILLING CO., INC. by (signature) Mora Keller					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.					
NOM 040-1414		CHECK. W	пе сору, ∐ Ві	ue Copy, 🔲 Pink Copy	

29,856

The Professionals MINTER-WILSON DRILLING CO.

Irrigation and Domestic Water Systems Complete Installation and Repairing

INCORPORATED

Phone 620-276-8269 P.O. Box A **GARDEN CITY, KANSAS 67846**

NAME

WHEATLAND ELECTRIC - CIRCLE # G79

COUNTY

FINNEY

DATE

2-26-10

LOCATION:

NE 1/4 6-26-33 - FROM PARALLEL & IVANHOE ROAD - 1/2 MILE EAST

& 1/8TH OF A MILE SOUTHEAST

- NORTHWEST CORNER OF CIRCLE

STATIC WATER LEVEL -

TEST #2

0' TO 13' - FINE SAND

13' TO 22' - BROWN CLAY

22' TO 35' - FINE TO MEDIUM SAND & GRAVEL

35' TO 107' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH STRIPS OF BROWN CLAY

107' TO 110' - HARD WHITE CLAY & ROCK - 300 PULL DOWN

110' TO 125' - FINE TO MEDIUM SAND & GRAVEL - SOME COARSE

WITH LAYERS OF BROWN CLAY

125' TO 197' - FINE TO MEDIUM SAND & GRAVEL WITH STRIPS OF BROWN CLAY

197' TO 203' - BROWN CLAY

203' TO 216' - FINE TO MEDIUM SAND & GRAVEL WITH LAYERS OF BROWN CLAY

216' TO 230' - BROWN SANDY CLAY WITH STRIPS OF GRAVEL

230' TO 256' - FINE TO MEDIUM SAND & GRAVEL

WITH LAYERS OF BROWN SANDY CLAY

256' TO 264' - BROWN SANDY CLAY WITH STRIPS OF GRAVEL

264' TO 283' - BROWN SANDY CLAY

283' TO 303' - FINE TO MEDIUM SAND & GRAVEL

303' TO 331' - BROWN SANDY CLAY

331' TO 355' - FINE TO MEDIUM SAND WITH STRIPS OF BROWN SANDY CLAY 30%

355' TO 365' - BROWN SANDY CLAY WITH STRIPS OF SAND

365' TO 388' - BROWN CLAY

388' TO 407' - BROWN SANDY CLAY WITH STRIPS OF SAND

407' TO 415' - FINE TO MEDIUM SAND

415' TO 427' - BROWN CLAY WITH STRIPS OF WHITE ROCK

427' TO 441" - HARD BROWN CLAY

441' TO 448' - FINE TO MEDIUM SAND & BROWN ROCK MIXED

448' TO 462' - HARD BROWN CLAY

462' TO 466' - FINE TO MEDIUM SAND & BROWN ROCK MIXED

466' TO 470' - HARD BROWN CLAY

470' TO 475' - SHALE